

## **TABLE OF CONTENTS**

PANELS	Panel Guide	1-1
	Exposed Fastener Panels	1-2~1-6
	Concealed Fastener Panels	1-7 ~ 1-8
	Mechanically Seamed Panels	1-9 ~ 1-10
	Siding Panels	1-11
	Wall Panels	1-12 ~ 1-13
	Polycarbonate Panels	1-14
TRIM	Magna Rib / Delta Rib	2-1
	Corrugated	2-2
	PBR	2-3
	Loc Seam (Roof)	2-4
	Loc Seam (Wall), Chimney/Skylight, Universal	2-5
	Clip Loc	2-6
	MI-150	2-7
	MI-210 / MI-275	2-8
	Seamless Siding, Flush Panel	2-9
FASTENERS	Standard Wood Screws, Lag Bolts, Panel Clips	3-1 ~ 3-2
	Standard Tek Screws, Rivets, Roofing Staples	3-3 ~ 3-4
	Specialty Screws	3-5
	Framing Bolt Assemblies, Concrete Anchors	3-6
INSULATION & UNDERLAYMENT	Vapor Barrier, Dripstop	4-1
	Foil Insulation, WMP-VR Blanket Insulation	4-2
	Insulation Tapes	4-3
	Hybrid Underlayment, Ice & Water Shield	4-4
CLOSURE & SEALANTS	Solid Closure, Expanding Foam	5-1
	Vented Closure, Snap-Z, Screen Vent	5-2
	Nova Flex, Butyl Tape	5-3
PIPE FLASHINGS & EXHAUST VENTS	Silicone Flashings, EPDM Flashings	6-1
	EPDM Retrofit, EPDM Severe Slope, CoVent Exhaust Vents	6-2
DOORS	Entry Doors	7-1
	Sliding Door Hardware	7-2
	Dutch Doors	7-3
	Commercial Overhead Doors	7-4~7-5
	Residential Overhead Doors	7-6~7-7
ACCESSORIES	Touch-Up Paint, Gutter Protection	8-1
	Snow Retention	8-2
	Cupolas, Weathervanes	8-3
	Horse Stall Components	8-4
TOOLS	Snips	9-1 ~ 9-3
10013	Folding & Crimping	9-4~9-5
	Saw Blades	9-6
	Punches & Notchers	9-7
	Drivers	9-8
	Drill Bits	9-9
	Cordless Tools	9-10 ~ 9-19
	Miscellaneous Tools	9-20 ~ 9-22
	Safety & PPE	9-23
	Rental Equipment	9-24 ~ 9-25

Issued January 2025

"Live Every Day for Jesus!"



METALLION INDUSTRIES PANEL PRODUCTS							
	GAUGE	COVERAGE	APPLICATION	FINISH			
Traditional Metal Roof & Wall Panels (Exposed Fasteners)							
MAGNA RIB	29 / 26 <sup>*</sup>	36"	ROOF & WALL	PAINTED & GALV			
DELTA RIB III	29 / 26 <sup>*</sup>	36"	ROOF & WALL	PAINTED & GALV			
DELTA RIB II	29	24"	ROOF & WALL	PAINTED & GALV			
CORRUGATED	29	24" (21" roof)	ROOF & WALL	PAINTED & GALV			
PBR	26 / 24 <sup>*</sup>	36"	ROOF & WALL	PAINTED & GALV			
Re	sidential & Comme	rcial Roof Panels (Con	cealed Fasteners)*	*			
LOC SEAM	26 / 24 <sup>*</sup>	12" / 16"	ROOF	PAINTED			
CLIP LOC	26 <sup>*</sup> / 24	17-5/8"	ROOF	PAINTED			
MECHANICAL SEAM	24	16" / 17-1/2" / 18"	ROOF	PAINTED			
Se	amless Metal Soffi	t & Siding Panels (Con	cealed Fasteners)*	*			
FLUSH PANEL	26 / 24	12"	SOFFIT & WALL	PAINTED			
BOARD & BATT	26 / 24 <sup>*</sup>	11-3/4"	WALL	PAINTED			
STANDARD LAP	26 / 24 <sup>*</sup>	11-3/4"	WALL	PAINTED			
DUTCH LAP	26 / 24 <sup>*</sup>	11-3/4"	WALL	PAINTED			
METALINE <sup>1</sup>	26 / 24 <sup>*</sup>	12" / 16"	WALL	PAINTED			
DUTCH LAP		11-3/4"	WALL	PAINTED			

Non-Standard Gauge – See Sales Agent for Details

Full Length Panels can be Manufactured at your Jobsite - See Sales Agent for Details and Limitations

<sup>1</sup> Jobsite forming of Metaline profiles not available

Metallion Industries' roll-formed steel roofing and siding panels are engineered and manufactured to provide your structure with superior protection against the elements, resulting in long-lasting beauty and performance.


All of our premium panel lines utilize only high-quality steel and coatings, with each panel visually inspected at the time of manufacturing to ensure that you receive only the best. See our website below for our paint warranty information and more.

Please contact our friendly and knowledgeable staff today to discuss how we can enhance your next building project!

#### **EXPOSED FASTENER PANELS**

"Your Metal Roofing & Siding Supplier!"





# **MAGNA RIB**

Magna Rib is our most popular panel due to its versatility, economic value, and unique design. Reinforced major ribs not only strengthen the panel but improve panel alignment during installation. This 36" panel is most often used on pole barns, sheds, and other light industrial buildings.

Now available with DripStop<sup>™</sup> factory applied condensation control coating!


Contact us to learn more.



- Full 36" net coverage
- Purlin-bearing edge for strength and speed while fastening side laps
- Anti-siphoning side lap
- 8 intermediate stiffening ribs add extra strength to this panel
- Custom lengths 1' through 50' in cut-to-length one inch increments
- For color availability, additional specifications, and other information, please contact us or visit our website: www.metallionindustries.com

METALLION

## **EXPOSED FASTENER PANELS**



# **DELTA RIB III**


The Delta Rib III profile has a long history, making it a good match for many of your remodel projects. Our minor improvements to the rib design and the added anti-siphon lap give this classic panel an edge on strength and moisture protection. This 36" coverage panel is frequently used for both roof and walls on pole barns, shops, and other outbuildings.

- Full 36" net coverage
- Purlin-bearing edge for strength and speed while fastening side laps
- Anti-siphoning side lap
- 4 intermediate stiffening ribs add strength to this panel
- Custom lengths 1' through 50' in cut-to-length one inch increments
- For color availability, additional specifications, and other information, please contact us or visit our website: www.metallionindustries.com

#### **EXPOSED FASTENER PANELS**

"Your Metal Roofing & Siding Supplier!"





# **DELTA RIB II**


Delta Rib II is an exposed fastener panel that is designed to carry heavier loads than a similar design in the 3' wide panel; perfect for the job that requires more strength. These narrow panels are more accommodating for steep-sloped roof installations or one man crews.



1-4

1ETALLION

## **EXPOSED FASTENER PANELS**



# CORRUGATED

The history of corrugated metal panels reaches back almost 200 years. Having survived the test of time, they are still in demand today – especially for those wanting to maintain a rustic, traditional appearance. Our 2-1/2" Corrugated panels are only 26" wide, making them more accommodating for one-man crews.




- Full 24" net coverage for siding applications
- 21" net coverage for roofs
- Through fastened panel for roofing or siding
- Custom lengths 2' through 50' in one inch increments
- Traditional style looks great in agricultural, light industrial or residential applications
- For color availability, additional specifications, and other information, please contact us or visit our website: www.metallionindustries.com

#### **EXPOSED FASTENER PANELS**

"Your Metal Roofing & Siding Supplier!"





PBR

The PBR profile excels in commercial and industrial applications. Our PBR is made with heavy gauge steel – allowing panels to span up to five feet on purlins. The tall ribs not only increase load bearing capabilities, but deter water from siphoning under the overlap rib, making PBR ideal for low-sloped commercial roofs.

Now available with DripStop<sup>™</sup> factory applied condensation control coating!


Contact us to learn more.



- Full 36" net coverage
- Excellent for commercial and industrial applications
- 26 gauge high tensile (80 ksi) steel
- PBR panels require a minimum slope of 0.5:12
- UL90 rating when attached to steel purlins
- Custom lengths 1' through 50' in cut-to-length one inch increments
- For color availability, additional specifications, and other information, please contact us or visit our website: www.metallionindustries.com

#### METALLION INDUSTRIES

#### **CONCEALED FASTENER PANELS**



# LOC SEAM

Loc Seam is especially popular with insulated buildings because concealing the fasteners greatly reduces the chance that a failed washer will result in an expensive leak. A "concealed fastener" panel not only reduces maintenance concerns by protecting fasteners from the elements, but the smooth design allows debris from trees to wash or blow off the roof more easily – reducing the frequency of roof cleanings.



- Full 12" or 16" net coverage
- Easy installation and low maintenance
- Residential / Commercial applications
- No exposed fasteners
- Installed over solid substrates with underlayment
- On-site roll forming to custom lengths available
- Direct fastened—no clips necessary
- Factory notching available for hemming at the eave
- For color availability, additional specs, or other information, please contact us or visit our website

# 

# **CLIP LOC**


Clip Loc panel is a snap-together panel (no seaming required) designed for commercial, light structural or residential applications. The commercial wide pan look is not only aesthetically pleasing but engineered to exceed most wind load requirements in the country.



\*Oil Canning: Flat metal surfaces can display waviness, commonly referred to as "oil canning", which is an inherent characteristic of steel. "Oil canning" is not a defect and therefore not an acceptable reason for rejection.

- 17-5/8" net coverages available
- 24 ga standard pre-painted G-90 or AZ-50 (22 gauge optional)
- Factory notching available for hemming at the eave
- On-site roll forming to custom lengths available
- The clip design allows for unlimited thermal movement
- Optional factory or field-applied side lap sealant
- Weathertight warranty option
- Can be applied over solid substrates, steel decking with polyiso, or in limited applications over open purlins
- For color/custom coil availability, additional specs, or other information, please contact us or visit our website

### **MECHANICALLY SEAMED PANELS**



(shown with striations - also available with flat pan\*)

## MECHANICAL SEAM: MI-150 & MI-210

Our mechanically seamed panels, designed for architectural and commercial applications, are available in different configurations to accommodate a large variety of situations. The commercial wide pan look is not only aesthetically pleasing but engineered to exceed most wind load requirements in the country.




1ETALLION

"Your Metal Roofing & Siding Supplier!"

#### MECHANICALLY SEAMED PANELS


"Your Metal Roofing & Siding Supplier!"





## **MECHANICAL SEAM: MI-275**


Our mechanically seamed panels, designed for architectural and commercial applications, are available in different configurations to accommodate a large variety of situations. The commercial wide pan look is not only aesthetically pleasing but engineered to exceed most wind load requirements in the country.






## SIDING

Standard Lap



# **SEAMLESS SIDING**

Designed with minimal maintenance and longevity in mind, our durable 26-gauge steel siding is a sound investment. Our siding conceals the fasteners, creating a sleek, clean appearance. No unsightly caulking, lapping, or painting patchwork required. On site roll-forming makes long, seamless panels a reality!




 WALL PANELS
 Your Metal Roofing & Siding Supplier

 Image: Constraint of the state o

# **FLUSH PANEL**


Flush Panel is a concealed fastener system for creating sleek, smooth walls, vented soffits, or simple and attractive fascia coverings. Our Flush Panel gives you an aesthetic option. Typically made using 24 gauge steel — you may rest assured that your Flush Panel application has the utmost durability.



- Full 12" net coverage
- Attractive choice for wall, fascia, & soffit applications
- Can be installed vertically or horizontally
- Concealed fastening system
- Perforations available for vented soffit applications
- On-site roll forming to custom lengths available
- Adjustable reveal: from 0" to 3" in ½" increments
- Standard flat pan; available with beads or striations
- For color availability, additional specs, or other information, please contact us or visit our website



## WALL PANELS



# METALINE ARCHITECTURAL WALL PANELS

## AT A GLANCE



Sleek designs and varying shadow lines for a memorable and distinct appearance

- Available in 24ga. & 26ga. with a wide variety of colors for beauty & durability
- Concealed fastener system (no screws showing)

 Baked-on, long-life finishes and low maintenance ensures cost savings over conventional siding



#### POLYCARBONATE

POLYCARBONATE PANEL AVAILABLE PROFILES & LENGTHS					
	SKU	COVERAGE	LENGTH	COLOR	
MAGNA RIB	PMPOLYCLR	36"	Custom (max. 20')	CLEAR	
MAGNA RIB	PMPOLYWHI	36"	Custom (max. 20')	SOFT WHITE	
PBR	PPPOLYCLR	36"	Custom (max. 20')	CLEAR	
PBR	PPPOLYWHI	36"	Custom (max. 20')	SOFT WHITE	
DELTA RIB III	PD3POLYCLR10	36"	10′	CLEAR	
DELTA RIB III	PD3POLYWHI10	36″	10'	SOFT WHITE	
DELTA RIB III	PD3POLYCLR12	36"	12'	CLEAR	
DELTA RIB III	PD3POLYWHI12	36"	12'	SOFTWHITE	
CORRUGATED	PCPOLYCLR12	24"	12'	CLEAR	
CORRUGATED	PCPOLYWHI12	24"	12'	OPAL WHITE	
DELTA RIB II	PDPOLYCLR10	24"	10'	CLEAR	
DELTA RIB II	PDPOLYWHI10	24"	10'	OPAL WHITE	
DELTA RIB II	PDPOLYCLR12	24"	12'	CLEAR	
DELTA RIB II	PDPOLYWHI12	24"	12'	OPAL WHITE	

# POLYCARBONATE PANEL

Our polycarbonate panels are an ideal choice for adding natural lighting to your next exposed fastener panel clad project.. Constructed of true polycarbonate material, our panels offer superior longevity and performance when compared to fiberglass, PVC, or vinyl offerings. Choose maximum light transmissibility with our Clear panels (90%), or choose a balance of transmissibility and diffusion with our Soft White (85%) or Opal White (45%) panels.



# AT A GLANCE

- Available in Clear (90% light transmission), Soft White (85% light transmission), & Opal White (45% light transmission)
- Superior UV and impact resistance as compared to traditional fiberglass panels
- Resistant to developing discoloration or becoming brittle over time
- Our skylight panels are manufactured of true polycarbonate material. This is superior in longevity and performance to PVC or vinyl panels.
- PBR & Magna Rib profiles available in custom lengths up to a maximum of 20' per panel


1-14


(503) 630 - 7740 📕

ASKUS@METALLIONINDUSTRIES.COM




## MAGNA RIB / DELTA RIB





UPPER FLASH *	SIDE WALL TRIM	CHIMNEY COUNTERFLASH	CORNER (INSIDE & OUTSIDE)
3-1/2" 12"	3-1/4" 4-1/2" <u>1-1/8"</u> <u>3/4"</u>	3-1/2"	3-7/8" 1" 3/4" Inside Outside
SKU TMUF	SKU TMSW	SKU TMSKC	SKU TMCI SKU TMCO




TRACK COVER	DOUBLE TRACK COVER	RODENT GUARD	BASE TRIM
1-5/8" 1-3/4" 7" 1-1/4"	1-3/4" 2-3/8" 7-1/2" 5" 1-1/4"	1-3/8"	2-1/4"
SKU TMTC	SKU TMTCD	SKU TMRO	SKU TMB


All trim is in 10'-3" lengths - up to 20'-3" lengths available in 2' increments




## CORRUGATED



"Your Metal Roofing & Siding Supplier!"



UPPER FLASH *	SIDE WALL TRIM	CHIMNEY COUNTERFLASH	CORNER (INSIDE & OUTSIDE)
3-1/2" 12" SKU TCUF	3-1/4" 5-1/2" <b>SKU TCSW</b>	5/8" 3-1/2" <u>SKU TCSKC</u>	4" 4" 4" 4" Inside Outside SKU TCCI SKU TCCO



TRACK COVER	DOUBLE TRACK COVER	RODENT GUARD	BASE TRIM
1-5/8" 1-3/4" 7" 1-1/4"	1-3/4" [ 2-3/8" 7-1/2" 5" 1-1/4"	2-1/8"	2-3/8" 5/8" 5/8"
SKU TCTC	SKU TCTCD	SKU TCRO	SKU TCB


All trim is in 10'-3" lengths - up to 20'-3" lengths available in 2' increments



#### PBR

RIDGE CAP *	FORMED RIDGE CAP *	TOP SHED *	GABLE TRIM
8" 3/4" 1-1/4"		5-1/2"	5-1/2"
SKU TPRI	36" x 36" Coverage SKU TPRIF	SKU TPTOP	SKU TPG

EAVE FLASH *	ENDWALL-TO-ROOF *	PITCH CHANGE (UPPER & LOWER) *	W-VALLEY *
5-1/2"	4-1/4"	6-1/2" 6-1/2" Lower Upper	9-1/4" 1-1/2" L
SKU TPEV	SKU TPEW	SKU TPPCL SKU TPPCU	SKU TPWV



C-CASING (CLOSED)	C-CASING (OPEN)	С ЈАМВ	L JAMB
1-3/8"	1-3/8"	3″ S"	3" CHOOSE WIDTH
2-5/8″	2-7/8″	WIDTH:         6"         SKU         TPJC6           WIDTH:         8"         SKU         TPJC8	WIDTH:         6"         SKU         TPJL6           WIDTH:         8"         SKU         TPJL8
SKU TPCCC	SKU TPCCO	WIDTH: 10" SKU TPJC10	WIDTH: 10" SKU TPJL10

TRACK COVER	DOUBLE TRACK COVER	RODENT GUARD	BASE TRIM
2-1/4" 1-3/4" 7" 1-1/4"	2-1/2" 2-3/8" 7-1/2" 5" 1-1/4"	2-3/4"	3-5/8"
SKU TPTC	SKU TPTCD	SKU TPRO	SKU TPB


All trim is in 10'-3" lengths - up to 20'-3" lengths available in 2' increments


## LOC SEAM (ROOF)


2-4

"Your Metal Roofing & Siding Supplier!"










PITCH CHANGE UPPER & LOWER *	PITCH CHANGE CLOSED *	ENDWALL-TO-ROOF & CLOSED *	SIDEWALL & COMPENSATING
6-1/2"	6-1/8" 6-1/2" 77/8"	8" 3-1/4" 2-7/8" 5-1/2" 5-1/2" 7/8" 5-1/2"	2-3/4" 2-1/2" 2" 3" 7/8" 7/8"
Lower Upper	Closed Lower Closed Upp	Open Endwall Closed Endwall	Sidewall 3" Comp. Sidewall
SKU TLPCL SKU TLPCU	SKU TLPCLC SKU TL	CUC SKU TLEWO SKU TLEWC	SKU TLSW SKU TLSWC




All trim is in 10'-3" lengths - up to 20'-3" lengths available in 2' increments



# LOC SEAM (WALL)

	C CAS	SING		IN	ISIDE CORI	NER (3 PIE	CE)	OU	TSIDE CO	RNER (3 PII	ECE)	Z TR	ANSITION	
7/8"	7/8"	3 <sup>n</sup>	PAINT	OPEN	4-5	1″	-1/4″	4-5/8	ر عرب ا	3-1/4" "	EN	2-3/4″	1"	
				Corner	Channel	Inside	e Corner	Corner	Channel	Outside	Corner		U	
		SKU	TLCC	SKU	TLCCOR	SKU	TLCCI3	SKU	TLCCOR	SKU	TLCCO3		SKU	TLZT



# CHIMNEY/SKYLIGHT

CHIMNEY COUNTERFLASH	CLOSED LOWER FLA	SH *	CLOSED UP	PER FLASH	*	SIDEW/	ALL FLASH	
5/8" 3-1/2"	2-1/2" OR 4-1/2" 5-1/2"	7/8″	3-1/2" OR 5-1/2"	12"		2-1/2" OR 4-1/2"	2″	,
	CURB HEIGHT: 4" SKU	TLSKL4	CURB HEIGHT: 4"	SKU	TLSKU4	CURB HEIGHT: 4"	SKU	TLSKS4
SKU TLSKC4	CURB HEIGHT: 6" SKU	TLSKL6	CURB HEIGHT: 6"	SKU	TLSKU6	CURB HEIGHT: 6"	SKU	TLSKS6







All trim is in 10'-3" lengths - up to 20'-3" lengths available in 2' increments


METALLION INDUSTRIES


## CLIP LOC




"Your Metal Roofing & Siding Supplier!"











All trim is in 10'-3" lengths - up to 20'-3" lengths available in 2' increments


\* Specify pitch when ordering



## MI-150









PITCH CHANGE (UPPER & LOWER) *	W-VALLEY *	Z CLOSURE
8-5/8" 7" OPEN 7 OPEN 7 OP	OPEN 10-1/2"	1-1/4"
Lower Upper		
SKU TM1PCL SKU TM1PCU	SKU TM1WV	SKU TM1Z

All trim is in 10'-3" lengths - up to 20'-3" lengths available in 2' increments




# MI-210 / MI-275





CHIMNEY COUNTERFLASH	ENDWALL-TO-ROOF *	SIDEWALL TRIM	HIP CAP *
5/8" 3-1/2"	3-1/8"	4-1/4" <u>3</u> " 1-7/8"	7-1/2" OPEN -7
SKU TM2SKC	SKU TM2EW	SKU TM2SW	SKU TM2H

TRIN	VI CLEAT &	OFFSET C	LEAT	PITCH	CHANGE (	JPPER & L	OWER) *	W-VALLEY *	W-VALLEY (CLEATED) *
2"	1/2″		/2" 1-3/4"	8-5/8″		7"	7" PEN 7	10-1/2" 1"	4-1/8" 5-1/2" 3/4"
Clea	at	Offset	Cleat	Lov	wer	Up	per		
SKU	TM2TC	SKU	TM2OC	SKU	TM2PCL	SKU	TM2PCU	SKU TM2WV	SKU TM2WVC





All trim is in 10'-3" lengths - up to 20'-3" lengths available in 2' increments


\* Specify pitch when ordering



# SEAMLESS SIDING








# **FLUSH PANEL**

INSIDE CORNER (3 PIECE)	OUTSIDE CORNER (3 PIECE)	INSIDE CORNER	OUTSIDE CORNER
OPEN 7 4-5/8" 1-1/8" 3-1/4"	OPEN 3-1/4" 4-5/8"	3-1/2"	3-1/2" 
Corner Channel Inside Corner	Corner Channel Outside Corner		
SKU TFCCOR SKU TFCCI	SKU TFCCOR SKU TFCCO3	SKU TFCI	SKU TFCO



All trim is in 10'-3'' lengths - up to 20'-3'' lengths available in 2' increments



#### STANDARD WOOD SCREWS

Quantity



- #10 diameter industry standard for panel fastening
- Bonded EPDM washer for a consistent, weather tight seal
- Weather coating for supreme corrosion resistance

Diamatan

 Stocked in plain (galvanized) and all of our standard paint colors (not every color stocked in 2" and above, may require special order)

ROO	F & WA	<b>.   (#1</b> (	0)

JKU	Diameter	Length	Quantity	Head Size
FW1	#10	1″	250	1/4″ Hex
FW15	#10	1-1/2″	250	1/4″ Hex
FW2	#10	2″	250	1/4″ Hex
FW25	#10	2-1/2″	250	1/4″ Hex
FW3	#10	3″	250	1/4″ Hex

I an adda

Sheet metal to sheet metal screw

CVII

- Used for side lap, ridge cap, and fastening various other trim pieces
- Bonded EPDM washer for a consistent, weather tight seal
- Weather coating for supreme corrosion resistance
- Stocked in plain (galvanized) and all of our standard paint colors

STITCHERS	SKU	Diameter	Length	Quantity	Head Size
STITCHERS	FWS	#12	3/4″	250	1/4″ Hex



- #14 diameter ideal for fastening into pre-existing fastener penetrations made with smaller diameter fasteners
- Bonded EPDM washer for a consistent, weather tight seal
- Weather coating for supreme corrosion resistance
- Stocked in plain (galvanized) and a subset of our standard paint colors (not every color in stock, some colors may require special order)
- \*2" length available by special order

	SKU	Diameter	Length	Quantity	Head Size
	FW1*14	#14	1″	250	5/16″ Hex
ROOF & WALL (#14)	FW15*14	#14	1-1/2″	250	5/16″ Hex
	FW2*14*	#14	2″	250	5/16″ Hex

(503) 630 - 7740 🛛 📕

#### STANDARD WOOD SCREWS

"Your Metal Roofing & Siding Supplier!"



- Designed for areas where a low profile is essential
- Recommended for our concealed fastener panels
- Weather coating for supreme corrosion resistance
- Use with our #2 square drive bits (TOOBITSQ)
- \*FWL34 available as standard panhead design

SKU	Diameter	Length	Quantity	Head Size
FWL34*	#10	3/4″	250	Combo
FWL1	#10	1″	250	#2 Square
FWL15	#10	1-1/2″	250	#2 Square
FWL2	#10	2″	250	#2 Square

- Used for fastening polycarbonate panels
- Oversize washer provides additional coverage and protection against leakage and cracking
- Weather coating for supreme corrosion resistance

SKU	Diameter	Length	Quantity	Head Size
FWP1GAL	#9	1″	250	1/4″ Hex
FWP15GAL	#9	1-1/2″	250	1/4″ Hex

- Ideal for use with fastening a selection of our sliding door hardware
- For fastening into wood only

SKU	Diameter	Length	Quantity	Head Size
DSLAG1415	1/4″	1-1/2″	To Order	3/8″ Hex
DSLAG382	3/8″	2″	To Order	1/2″ Hex

- For use with our line of Clip Loc and Mechanically Seamed panels
- Please consult with our sales agents for jobs requiring UL stamped clips

SKU	Profile	Substrate	Height	Width	Base
ACCLWOO	Clip Loc	Wood	1-7/8″	2-1/2″	
ACCLSTE	Clip Loc	Steel	1-7/8″	3-1/2″	
ACCL15FX	MI-150		1-1/2″	2″	Fixed
ACCL15FL	MI-150		1-1/2″	5″	Floating
ACCL2FX			2″	3″	Fixed
ACCL2FL	MI-210		2″	5″	Floating
ACCL25FX	MI-275	Insulation	2-1/2″	3″	Fixed
ACCL25FL		Insulation	2-1/2″	5″	Floating




#### **ULTRA LOW PROFILE**



## POLYSEAL (WOOD)



## LAG BOLTS



## PANEL CLIPS

## **STANDARD TEK SCREWS**

	<ul> <li>Used for pan fixing steel panels on walls and roofs to steel framing</li> </ul>							
	-	Has 9/16" outside	diameter w	asher	and rubbe	er seal		
	-	Weather coating f	or supreme	corro	sion resist	ance		
	<ul> <li>Stocked in plain (galvanized) and a variety of paint colors</li> </ul>							
	_	*2" and above leng	gths availab	le by s	pecial ord	er		
		SKU	Diameter	TPI	Length	Tip	Quantity	Head Size
		FD1	#12	14	1″	Т3	250	5/16″ Hex
		FD15	#12	14	1-1/2″	Т3	250	5/16″ Hex
		FD2*	#12	14	2″	Т3	250	5/16″ Hex
		FD25*	#12	14	2-1/2″	Т3	250	5/16″ Hex
ROOF & WALL (PAN FIX	ED)	FD3*	#12	14	3″	Т3	250	5/16″ Hex
1 hanne	<ul> <li>Lap screw used for sheet to sheet fastening of trim and panels</li> <li>Ideal for bonding lap seams in light gauge panels</li> <li>Weather coating for supreme corrosion resistance</li> <li>Stocked in plain (galvanized) and a variety of paint colors</li> </ul>							
~		SKU		TDI				
		SKU	Diameter	TPI	Length	Tip	Quantity	Head Size
LAP SCREWS		FDL	#14	1P1 14	Length 7/8″	Tip T1	Quantity 250	Head Size
LAP SCREWS	-		#14 Itall for all ra allations	14 aised o	7/8"	T1	250	5/16" Hex
	_	FDL Quick and easy ins seamed panel inst	#14 Itall for all ra allations or supreme	14 aised c	7/8" clip applica	T1 ations	250 with mecha	5/16" Hex
	-	FDL Quick and easy ins seamed panel inst Weather coating f	#14 Itall for all ra allations or supreme	14 aised c	7/8" clip applica	T1 ations	250 with mecha	5/16" Hex
		FDL Quick and easy ins seamed panel inst Weather coating for SKU FDRCLIP1 Designed for areas Recommended for trim without hang Weather coating for	#14 stall for all ra allations or supreme Diameter #12 s where a lo r attaching of ing up on a or supreme	14 aised c corro: TPI 14 w pro: c-casin traditi corro:	7/8" Clip application sion resistation Length 1" file is esse g to allow onal hex h sion resistation	T1 ations r ance Tip T3 ntial panel: nead	250 with mecha Quantity 250	5/16" Hex anically Head Size 5/16" Hex
RAISED CLIP SCREWS		FDL Quick and easy ins seamed panel inst Weather coating for SKU FDRCLIP1 Designed for areas Recommended for trim without hang Weather coating for #10 x 5/8" stocked	#14 Itall for all ra allations or supreme Diameter #12 s where a lo r attaching c ing up on a or supreme d in plain (ga	14 aised c corro: TPI 14 w pro c-casin traditi corro: alvaniz	7/8" Clip application sion resistant Length 1" file is esse g to allow onal hex h sion resistant ed)	T1 ations r ance Tip T3 ntial panel bead ance	250 with mecha Quantity 250	5/16" Hex anically Head Size 5/16" Hex to the
RAISED CLIP SCREWS		FDL Quick and easy ins seamed panel inst Weather coating for SKU FDRCLIP1 Designed for areas Recommended for trim without hang Weather coating for #10 x 5/8" stocked	#14 tall for all ra allations or supreme Diameter #12 s where a lo r attaching of ing up on a or supreme d in plain (ga Diameter	14 aised c corro: TPI 14 w pro: c-casin traditi corro: alvaniz TPI	7/8" clip application sion resistation Length 1" file is esse g to allow onal hex h sion resistation sion resistation ted) Length	T1 ations of ance Tip T3 ntial panelo bead ance Tip	250 with mecha Quantity 250 s to slide in Quantity	Head Size
RAISED CLIP SCREWS		FDL Quick and easy ins seamed panel inst Weather coating for SKU FDRCLIP1 Designed for areas Recommended for trim without hang Weather coating for #10 x 5/8" stocked	#14 Itall for all ra allations or supreme Diameter #12 s where a lo r attaching c ing up on a or supreme d in plain (ga	14 aised c corro: TPI 14 w pro c-casin traditi corro: alvaniz	7/8" Clip application sion resistant Length 1" file is esse g to allow onal hex h sion resistant ed)	T1 ations r ance Tip T3 ntial panel bead ance	250 with mecha Quantity 250	5/16" Hex anically Head Size 5/16" Hex to the
<image/> <section-header><section-header></section-header></section-header>		FDL Quick and easy insiseamed panel insteemed panel insteemed panel insteemed panel insteemed panel insteemed panel insteemed for sku FDRCLIP1 Designed for areases Recommended for trim without hange Weather coating for areases Recommended for trim without hange Weather coating for stocked SkU FDPAN58	#14 stall for all ra allations or supreme Diameter #12 s where a lo r attaching c ing up on a or supreme d in plain (ga Diameter #10	14 aised c corro: TPI 14 w pro c-casin traditi corro: alvaniz TPI 16	7/8" clip application sion resistation Length 1" file is esse g to allow onal hex h sion resistation ed) Length 5/8"	T1 ations r ance Tip T3 ntial panel: head ance Tip T2	250 with mecha Quantity 250 s to slide in Quantity To Order	<ul> <li>5/16" Hex</li> <li>Head Size</li> <li>5/16" Hex</li> <li>to the</li> <li>Head Size</li> <li>#2 Phillips</li> </ul>

#### **STANDARD TEK SCREWS**



- Used for fastening heavy duty structural framing
- Total steel thickness capacity of 0.036" to 0.250"
- Weather coating for supreme corrosion resistance



SKU	Diameter	TPI	Length	Tip	Quantity	Head Size	
FDF1T3	#14	14	1″	Т3	500	3/8″ Hex	FRAMING (T-3)

- Used for fastening heavy duty structural framing
- Used for drilling through thick or multiple layers of steel
- Total steel thickness capacity of 0.250" to 0.625"
- Ideal for double knee and apex bracing
- Weather coating for supreme corrosion resistance



SKU	Diameter	TPI	Length	Tip	Quantity	Head Size		
FDF15T5	#14	20	1-1/2″	T5	50	3/8″ Hex	FRAMING (T-5)	

- Provides a low visibility trim connection
- Suited for downspouts, gutters and corner trim
- Available in galvanized or a variety of colors



SKU	Size	Quantity	DIVETS	
FR*	1/8" x 5/16"	To Order	RIVEIS	

 Suitable for use with our DeWalt Carbon Fiber Hammer Tacker (TOOHTDEWALT) or other standard hammer tackers



SKU	Size	Quantity	
FST38	3/8" Chisel Pt.	5000	ROOFING STAPLES
3-4	(503) 630 - 7740	ASKUS@METALLIONINDU	STRIES.COM WWW.METALLIONINDUSTRIES.COM





- Designed for attaching wood to structural steel
- Countersunk head seats itself flush into the wood for easy top finishing
- Ideal for putting sub flooring on steel mezzanines
- Weather coating for supreme corrosion resistance

Comment								
		SKU	Diameter	TPI	Length	Tip	Quantity	Head Size
		FDWING1916	#10	24	1-9/16″	Т3	To Order	#2 Philips
		FDWING214	#12	24	2-1/4″	T4	To Order	#2 Philips
WING DRILLER		FDWING3	#12	24	3″	T4	To Order	#2 Philips
							<u>.</u>	
	-	Used for crest fixing steel roof panels to steel framing						

- Has 9/16" outside diameter washer and rubber seal
  - Secondary thread under shank pulls metal upward preventing any water penetration
  - Weather coating for supreme corrosion resistance
  - Stocked in plain (galvanized) and a variety of paint colors

	SKU	Diameter	TPI	Length	Tip	Quantity	Head Size
	FDH178MS	#12	14	1-7/8″	Т3	250	5/16″ Hex
	FDH238MS	#12	14	2-3/8″	Т3	250	5/16″ Hex
ROOF (CREST FIXING)	FDH314MS	#12	14	3-1/4″	Т3	To Order	5/16″ Hex



- Special washer designed for crest fixing polycarbonate skylight panels
- Weather coating for supreme corrosion resistance

	SKU	Diameter	TPI	Length	Tip	Quantity	Head Size
	FDPOLY178	#12	14	1-7/8″	Т3	250	5/16″ Hex
POLYSEAL (STEEL)	FDPOLY238	#12	14	2-3/8″	Т3	250	5/16" Hex



- Used for general, light duty applications
- Total steel thickness capacity of 0.035" to 0.175"
- Weather coating for supreme corrosion resistance

LIGHT DUTY (UTILITY)	SKU	Diameter	TPI	Length	Tip	Quantity	Head Size
	FDF34T2	#12	14	3/4″	T2	250	5/16″ Hex

#### STANDARD WOOD SCREWS

"Your Metal Roofing & Siding Supplier!"



- The assembly has a flanged head and bolt, no washers needed
- ✓ 5/8" Conforms to ASTM A307 specifications
- 9/16" Conforms to Grade 5 specifications



SKU	Diameter	Length	Quantity	Head Size
FFB58114FL	5/8″	1-1/4″	25	15/16″ Hex
FFB916115FL	9/16"	1-1/2″	40	13/16″ Hex

- One-piece, vibration & tamper resistant anchor
- Formed with an "S" shaped configuration to create an expansion mechanism
- Typically used for base angles and door jamb base brackets



**FLANGED BOLT & NUT** 

SKU	Diameter	Length	Quantity	
FCSPIKE141	1/4″	1″	TO ORDER	

- Low installation torque in concrete and masonry base materials
- Patented thread design offers toughened threads for tapping high strength concrete
- Universal product for concrete and grouted/solid masonry
- Designed for use with ANSI standard tolerance drill bits
- Can be installed closer to a free edge than traditional expansion anchors
- Ratchet teeth on underside of hex washer head lock against fixture


SKU	Diameter	Length	Quantity
FCWBD123	1/2″	3″	To Order
FCWBD125	1/2″	5″	To Order
FCWBD585	5/8″	5″	To Order



# SCREW BOLT PLUS




#### **VAPOR BARRIER**



- Excellent choice as an in-wall and roof vapor retarder
- Heavy-duty scrim reinforcement, laminated between two layers of virgin high-strength polyethylene film
- Resists punctures and immediately stops tears
- Accordion folded and tightly rolled on a heavy-duty core for ease of handling and time-saving installation
- UV stabilizers increase longevity
- \*20' width available by special order

	SKU	Width	Length	R-Value	Thickness
	V600DS	6′	100′	None	6 mil
VAPOR BARRIER	V1200DS	12′	100′	None	6 mil
VAPOR BARKIER	V2000DS*	20′	100′	None	6 mil



Dripstop is an optional condensation control coating that can be applied to our **Magna Rib** and **PBR** panel profiles at the time of manufacturing.

- Eliminates need for separate vapor barrier installed between panel and substrate cutting down on construction time and cost
- Highly durable. Rip & tear resistant.
- Protects panel underside coating, resulting in increased corrosion resistance
- Eliminate bird nesting troubles commonly encountered with traditional blanket barriers
- Inquire with our sales agents to find out if Dripstop is right for your next project

	Panel Profile	Coverage
	Magna Rib	36″
DRIPSTOP PANEL COATING	PBR	36″

#### INSULATION



- Non-toxic, no fiberglass
- Seals tight around fasteners
- Certified ASTM testing
- Microcell polyethylene foam construction
- Improves energy efficiency
- Vapor barrier and thermal break all in one
- EZ Seal tape flange



SKU	Width	Length	Facing	R-Value (varies by application)	
IFLE4125	4′	125′	Foil / Foil	Up to R-11	
IFLE684	6′	84′	Foil / Foil	Up to R-11	
IFLEW4125	4′	125′	Foil / White	Up to R-11	
IFLEW684	6′	84′	Foil / White	Up to R-11	

## **FOIL INSULATION**

- Fiberglass insulation bonded to white reinforced vinyl backing
- Insulates against the cold
- Eliminates condensation and drafts, reduces noise
- Cut-to-length
- \*IC600 stocked in 6' x 100' lengths

SKU	Width	Max Length	R-Value	Thickness
IC600*	6′	100′	R7	2″
IW1RN	4' or 6'	100′	R7	2″
IW3R10	4′ or 6′	50′	R10	3″
IW4R13	4' or 6'	50′	R13	4″
IW6R19	4' or 6'	50′	R19	6″
IW8R25	4' or 6'	40′	R25	8″



## WMP-VR BLANKET



	SKU	Width	Length	Rei
-	High tack, high adhesion, h Excellent low and elevated ATADSGS bonds well in hig	temperature pe	rformance	

	SKU	Width	Length	Reinforced	
DOUBLE SIDED TAPE	ATADS	1.5″	180′	No	
DOUBLE SIDED TAPE	ATADSGS	1.5″	180′	No	



- Thin, strong, conformable, premium vinyl tape
- Particularly aggressive acrylic adhesive system
- Shrink and plasticizer resistant

	SKU	Width	Length	Reinforced
	ATAV	3″	150′	No
VINYL TAPE	ATAVR	3″	150′	Yes



- Thin, strong, conformable, premium foil tape
- Particularly aggressive acrylic adhesive system
- Shrink and plasticizer resistant

FOIL TAPE				SKU		Width	Length		Reinforced
FUILTA	<b>NPE</b>		,	ATAFR		3″	150′		Yes
(503) 630 - 7740		ASKUS@METALLIONINDL	STRIES.COM		WWW.ME	TALLIONINDUSTRIES	.COM		4-3

#### UNDERLAYMENT

"Your Metal Roofing & Siding Supplier!"



- Hybrid technology combines asphaltic polymer & synthetic fabrics
- Higher strength than traditional underlayment & wrinkle free, even when soaking wet
- Use in high wind areas where other products blow off
- Nail sealable
- Limited lifetime extended warranty
- Approximate weight per roll is 40 lbs.



SKU	Width	Length	Coverage		
UHYBWEACXL	3.1′	145′	~450 sq ft		

- Ideal for high temperature applications (up to 265°F)
- Peel and stick application
- Ideal for applications under metal, tile, & other roof systems
- Meets or exceeds ASTM D1970 requirements
- Protects against wind driven rain & water intrusion
- Protects against ice & water dams
- Protects against spread of fire
- 30 year warranty
- Approximate weight per roll is 70 lbs.



SKU	Width	Length	Coverage	HT3 ICE & WATER
UICEHT3	3.3′	66.8′	~220 sq ft	HISICE & WATER



- Made of crosslink polyethylene foam coated for enhanced UV resistance and durability
- 1/4" adhesive beads eliminate installation blow-away and adheres in subfreezing temperatures and on wet surfaces.
- Provides a block against moisture and insects

GREET		SK		
	Profile	Inside	Outside	Length
	Clip Loc	n/a	CSCL	36″
	Corrugated	CSC		24″
	Delta Rib II (24")	CSDI	CSDO	24″
	Delta Rib III (36")	CSDELTA3I	CSDELTA3O	36″
	Loc Seam (12")	n/a	CSL12O	36″
	Loc Seam (16")	n/a	CSL16O	32″
	Magna Rib	CSMI	CSMO	36″
	PBR	CSPI	CSPO	36″
	Pro Panel II	CSPRO2I	CSPROO	36″
	Ultra Loc	CSULTRAI	n/a	32″
		1		



- EMSEAL Metal Roof & Metal Building Sealant Tape
- Stocked in AST Hi-Acrylic (Black)
- Will not dry out and become hard or brittle
- UV-stable and highly resistant to aging and vermin (bugs, rodents, birds, etc.)
- Provides a durable and versatile solution to these typically difficult-toseal panel contours at eaves, hips, valleys, peaks, concealed gutters, etc.

	SKU	Height	Width	Length
	CSEMSASH252506	1″	1″	19.68′
	CSEMSASH402504	1-1/2″	1″	13.12′
EXPANDING FOAM	CSEMSASH502504	2″	1″	13.12′

(503) 630 - 7740

#### **VENTED CLOSURE**

"Your Metal Roofing & Siding Supplier!"



- Provides for ventilation at ridge while guarding against moisture and insect intrusions
- Won't absorb moisture, helping to prevent against blockage due to freezing
- Proprietary adhesive for superior hold
- Easy one-person installation

		SKU				
	Profile	Non-Profiled	Profiled	Thick.	Width	Length
	Clip Loc	CVCL	n/a	2″	2″	20′
D	elta Rib III (36")	CVMN	n/a	1″	2″	20′
L	.oc Seam (12")	n/a	CVL12	1.5″	2″	12″
L	.oc Seam (16")	n/a	CVL16	1.5″	2″	16″
	Magna Rib	CVMN	CVM	1″	2″	20′
PBR CVPN		CVPN	CVP	1.5″	2″	20′



## **VENTED CLOSURE**

- Patented ridge vents designed for use with standing seam panel
- Provided in 26 ga. "ECO Black"
- Offers a clean, sleek appearance in addition to excellent performance
- 3/4" Butyl sealant strip pre-applied
- Class A fire rated; Can prevent blowing embers from entering the attic through the ridge vent

Profile	SKU	Height	Length
Clip Loc (17-5/8")	CVSZCL	1-3/4″	17-1/8″
Loc Seam (12")	CVSZL12	1″	11-1/4″
Loc Seam (16")	CVSZL16	1″	15-1/4″
MI-200 / MI-210	CVSZM2	2″	11-1/4″
MI-275	CVSZM27	2″	17-1/4″

- Wire mesh screen excellent for venting along a ridge
- Small mesh for allowing air flow while protecting against bird and insect intrusion



			acrit William
SKU	Width	Length	
CVSCR8	8″	100′	SCREEN VENT
5-2	(503) 630	- 7740	ASKUS@METALLIONINDUSTRIES.COM





NOVA

# **SEALANTS**

- Silicone sealant/adhesive available in translucent and select colors
- Remains permanently flexible and adheres well to damp surfaces
- Extrudes down to -20° F
- Meets CARB and OTC Regulation (UOC Compliant)
- For both SMP and PVDF paint applications

	SI	κυ	
Color	Cartridge (10oz.)	Sausage (20oz.)	
Clear	SNVFCLR	SNVFCLR20	
Black, Matte Black	SNVFBLA	SNVFBLA20	
Charcoal, Dark Gray	SNVFCHA	SNVFCHA20	
Dark Bronze	SNVFDBZ	SNVFDBZ20	
Forest Green	SNVFFOR	SNVFFOR20	
Gray	SNVFGRA	n/a	
Light Stone, Sandstone, Hickory	SNVFLST	n/a	
Medium Bronze	SNVFMBZ	n/a	
Sierra Tan	SNVFSIE	n/a	
White, Regal White	SNVFWHI	SNVFWHI20	
TI	P KIT		
2 Elbows, 2 Long Tips, 2 Caps	SNVFTIP		



**NOVA FLEX** 

- Excellent for sealing edges and seams on metal roofs
- Excellent flexibility over wide temperature ranges
- Long term durability

	SKU	Width	Thickness	Length	Bead
	SBCL12	1/2″	3/32″	50′	Single
	SBCL34	3/4″	1/8″	50′	Single
BUTYL TAPE	SBCL78D	7/8″	3/16″	40′	Double





- Great for residential or commercial heat vents and stove pipes
- Flexible base can be conformed to virtually any panel profile
- Maximum resistance to UV rays and weathering
- Easy on-site customization

				Pipe Outer Diameter		Base Dimensions	
		SKU	Size	Minimum	Maximum	Width	Length
		MFSIL4	#4	2-3/4″	7″	10″	10″
		MFSIL5	#5	4″	8-1/4″	11″	11″
		MFSIL6	#6	4-3/4″	10″	12″	12″
		MFSIL7	#7	5-1/2″	11-1/2″	14″	14″
		MFSIL8	#8	6-3/4″	13-1/2″	17″	17″
LICONE (HIGH TEMP)		MFSIL9	#9	9-1/2″	20-1/2″	25″	25″

- Great for residential or commercial pipes
- Flexible base can be conformed to virtually any panel profile
- Withstands temperatures up to 212° F

- Maximum resistance to UV rays and weathering
- Easy on-site customization special order a variety of colors

			Pipe Oute	r Diameter	Base Dimensions	
	SKU	Size	Minimum	Maximum	Width	Length
	MFEPD2	#2	7/8″	4″	6″	6″
	MFEPD3	#3	1⁄4″	5-3/4″	8″	8″
	MFEPD4	#4	2-3/4″	7″	10″	10″
	MFEPD5	#5	4″	8-1/4″	11″	11″
	MFEPD6	#6	4-3/4″	10″	12″	12″
	MFEPD7	#7	5-1/2″	11-1/2″	14″	14″
	MFEPD8	#8	6-3/4″	13-1/2″	17″	17″
	MFEPD9	#9	9-1/2″	20-1/2″	25″	25″



SIL

**EPDM** 

#### **PIPE FLASHINGS**

"Your Metal Roofing & Siding Supplier!"



- Flexible base can be conformed to virtually any panel profile
- Withstands temperatures up to 212° F
- Maximum resistance to UV rays and weathering
- Easy on-site customization residential or commercial pipes
- Useful for electrical weather-heads or any location where over-the-top fitting is not an option

		Pipe Outer Diameter		Base Din	nensions
SKU	Size	Minimum	Maximum	Width	Length
MFRET1	#1	1/2″	4″	8-3/16″	8-3/16″

- Angled design for easy installation and superior sealing on high slope roofs with pitches between 3:12 and 16:12
- Flexible base can be conformed to virtually any panel profile
- Withstands temperature ranges between -67° F and 212° F
- Maximum resistance to UV rays and weathering

Minimum

1/4"

Easy on-site customization — residential or commercial pipes

Pipe Outer Diameter

Maximum

5-3/4"

**Base Dimensions** 

Length

11"

Width

11"



# **EPDM SEVERE SLOPE**

**EPDM RETROFIT** 

# EXHAUST VENTS

Size

#1

- All-in-one exhaust fan vent designed for metal roofs
- Ideal for interior exhaust fans equipped with a 3" or 4" flex hose
- Comes packed and ready for install
- Includes Zip Tie for attaching the flex duct
- Extended edge prevents flex hose slipping off
- Not designed for dryer vents

SKU	Flex Pipe Dia.	Color
ACCOVENT3BLA	3″	Black
ACCOVENT4BLA	4″	Black
ACCOVENT4GRA	4″	Gray



6-2

SKU

MFPITCH1

COVENT





- Door only. Hardware sold separately to provide customization options.
- 3' width doors stocked in universal or inswing options. Note that inswing option is not ADA compliant.
- Raised threshold available with our inswing options offers enhanced protection against wind and water intrusion. Outswing option available via special order.
- Pre-hung
- Heavy duty 16ga. steel frame
- Full perimeter weather stripping
- Polar White color
- Customization options, such as panels, windows, and more are available. Contact us for details and options.

Door Dims		Rough Opening		
Width	Height	Width	Height	
3'-0"	6'-8″	38-5/8″	81-3/4″	
4'-0"	6'-8″	50-5/8″	81-3/4″	
6′-0″	6′-8″	75-13/16"	81-3/4″	

	Prep Level SKU		Holes		Doo	r Dims
	U1	U2	U1	U2	Width	Height
	DE9536U1NH	DE9536U2NH	1	2	3′-0″	6′-8″
Series 95 (Door Only)	DE9548U1NH	DE9548U2NH	1	2	4'-0"	6′-8″
	DE9572U1NH	DE9572U2NH	1	2	6'-0"	6'-8"

- For use with our line of Series 95 pre-hung entry doors (shown above)
- Grade 2 & 3 deadbolts & knobs available keyed alike or separately

Entres Control	SKU	Hardware	Grade
	DEDBG2	Deadbolt	2
	DEDBG3	Deadbolt	3
	DEDBHG	Deadbolt	High
	DEKG2	Knob	2
	DEKG3	Knob	3
Series 95 Hardware	DELC	Lever	Commercial
	DE95SCS	Series 95 Door N	Mount-To-Steel Fastener Pack





# **DUTCH DOORS**



We are proud to offer Dutch, Loft, and Bale Doors product lines from CannonBall:HNP.

These high quality door kits are suitable for all types of wood and metal buildings.

Fast and easy assembly and installation. All components and fasteners come finished and ready to install.

#### 2600 Series Doors:

- Available in both hinged and sliding models
- Traditional solid panel crossbuck upper and lower panel design, or replace upper panel with window lite
- Offered in both single and double door configurations
- Powder coated to match building colors
- Heavy duty steel framing

Additional configurations and product lines available. Please discuss your projects needs with our sales agents.





#### **COMMERCIAL OVERHEAD DOORS**

"Your Metal Roofing & Siding Supplier!"



- Designed for moderate commercial use
- Value priced
- Nominal 24 gauge steel construction
- Standard white smooth finish
- Optional R 7.6 Insulated panels with polylaminate back available (30 gauge steel back option available)
- Hi-lift, vertical lift, and roof pitch track available
- Low headroom radius track available down to 7" clearance
- Multiple standard and custom sizes available
- See wayne-dalton.com for a full list of options
- Manufactured by Wayne Dalton Made in USA



#### **COMMERCIAL MODEL CX-2400**

- True 24 gauge steel construction
- High strength for heavy-duty use
- Standard white smooth finish
- Optional R 7.6 Insulated panels with polylaminate back available (30 gauge steel back option available)
- Hi-lift, vertical lift, and roof pitch track available
- Low headroom radius track available down to 7" clearance
- Multiple standard and custom sizes available
- See wayne-dalton.com for a full list of options
- Manufactured by Wayne Dalton Made in USA



#### **COMMERCIAL MODEL CX-24**



# **COMMERCIAL OVERHEAD DOORS**



- Designed to accommodate large vehicles & equipment
- Strength & insulation without the traditional industrial look
- Thermal break helps ensure year-round energy efficiency
- Sound-absorbing insulation makes door quieter in operation & wind
- Multiple standard and custom sizes available
- See wayne-dalton.com for a full list of options
- Manufactured by Wayne Dalton Made in USA

#### **COMMERCIAL MODEL THERMOMARK 5000 SERIES**



- Virtually maintenance-free, weather-resistant, and sturdy
- Offered in a wide range of glass options and frame finishes
- Optional insulated rails & stiles
- Offer a combination of aesthetics, visibility, and light transmission
- Multiple standard and custom sizes available
- See wayne-dalton.com for a full list of options
- Manufactured by Wayne Dalton Made in USA

### COMMERCIAL MODEL FULL VIEW ALUMINUM



CHOOSE FROM A SELECTION OF AVAILABLE COMMERCIAL OPENERS TO SUIT YOUR DOOR & PROJECT

INQUIRE WITH OUR SALES AGENTS FOR MORE INFORMATION

#### **RESIDENTIAL OVERHEAD DOORS**

"Your Metal Roofing & Siding Supplier!"

- Designer style & enviable thermal efficiency
- Available in a variety of stylish panel options
- Now available with Wood Grain Impressions finish options
- Sound-absorbing insulation makes door quieter in operation & wind
- Multiple standard and custom sizes available
- See wayne-dalton.com for a full list of options
- Manufactured by Wayne Dalton Made in USA

#### **RESIDENTIAL MODELS 8300 & 8500**

- Beautiful aesthetics meet exceptional construction
- Offered in a wide range of glass options and frame finishes
- Tongue-and-groove joints provide a great weather barrier
- Optional insulation for added R-value
- Multiple standard and custom sizes available
- See wayne-dalton.com for a full list of options
- Manufactured by Wayne Dalton Made in USA



#### **RESIDENTIAL MODEL 8800 GLASS PANEL DOOR**

- Stunning doors add unique visual interest to your home's exterior
- Offered with mirrored, translucent, or opaque glass
- Tongue-and-groove joints provide a great weather barrier
- Ultra-modern look while being easy to maintain
- Multiple standard and custom sizes available
- See wayne-dalton.com for a full list of options
- Manufactured by Wayne Dalton Made in USA







## **RESIDENTIAL OVERHEAD DOORS**



#### Steel carriage house doors offer a richly embossed wood grain finish

- Structural reinforcements available for high-wind areas
- Thermal break helps ensure year-round energy efficiency
- Sound-absorbing insulation makes door quieter in operation & wind
- Multiple standard and custom sizes available
- See wayne-dalton.com for a full list of options
- Manufactured by Wayne Dalton Made in USA

#### **RESIDENTIAL MODEL 8600 CARRIAGE HOUSE STEEL DOORS**



- Stunning, handcrafted wooden carriage doors transform your home
- Classic swing-open appearance with modern sectional convenience
- Offered in a wide range of distinctive panel & facing designs
- Optional insulation for enhanced energy efficiency
- Multiple standard and custom sizes available
- See wayne-dalton.com for a full list of options
- Manufactured by Wayne Dalton Made in USA

#### **RESIDENTIAL MODEL 7400 SERIES CARRIAGE HOUSE WOOD DOORS**



CHOOSE FROM A SELECTION OF AVAILABLE RESIDENTIAL OPENERS TO SUIT YOUR DOOR & PROJECT

INQUIRE WITH OUR SALES AGENTS FOR MORE INFORMATION



# ACCESSORIES

Dura La Pana Ran	<ul> <li>Available in color in PVDF colors</li> <li>*Not all colors stor agents for color available in color available in color available.</li> </ul>	cked in bottles. Please	ations for both our SM e contact our customer	
		SKU	Container	Size

	SKU	Container	Size	
	ACPC	Brush Top Bottle*	2 oz.	
TOUCH-UP PAINT	АСРР	Pen	1/4 oz.	



- Individual pieces sold in 4' lengths
- Offered in 'Z Bend' (Wave) style
- The patented "Z" bends on the front and back of each piece ensure the product can be installed easily onto any gutter system
- Forget the hassle of cleaning and unclogging your gutters
- Protect against property damage
- Lifetime warranty

		Gutter Wid	dth SKU		
	4"	4-1/2″	5″	6″	Material
	ACGSZA4	ACGSZA45	ACGSZA5	ACGSZA6	Black Aluminum / Steel
GREEN GUTTER SCREEN	ACGSZS4	ACGSZS45	ACGSZS5	ACGSZS6	Black Steel

# **ACCESSORIES - SNOW RETENTION**

"Your Metal Roofing & Siding Supplier!"




- S-5 clamps are the industry leader in mounting solutions for standing seam metal roof panels
- Revolutionary design insert that prevents set screws from penetrating through metal roof panels
- Additional options available. Consult with our customer service agents to select the best clamp for your project needs
- Ideal for applications such as Solar Panel mounting
- Use with ColorGard snow retention products
- Ensure proper set screw installation in accordance with manufacturers instructions using our torque wrench and socket drive listed below.



SKU	Description	Panel Profile	
ACCS5N	S5N	Loc-Seam	
ACCS5S	\$5\$	Clip-Loc, Mechanical Seam (1" Rib Height)	1
ACCS5H	S5H	Clip-Loc, Mechanical Seam (2" Rib Height)	1
	Ir	istallation Tools	
TOOTW38D	3/8″	Drive, Dial Indicator Torque Wrench	
TOOBT3038		3/8" T30 Torx Socket Drive	

- For use with ColorGard Bracket (ACCS5CG)
- Consult with our customer service agents for products election and application for your project

SKU	Description	Panel Profile
ACCS5SC2	SnoClip II	Rib Height 1" to 1-1/2"
ACCS5SC3	SnoClip III	Rib Height 1-3/4" to 3-1/4"
ACCS5VC	VersaClip	
ACCS5VB47	Versa Bracket 47	Rib Height Maximum 1-3/4"
ACCS5FW1514	#14 x 1.5" ZAC Wood	Screw (Use w/ ACCS5VB47)



**CLIPS** 


For use with SnoClip II & III, VersaClip, and Versa Bracket 47

Description

ColorGard Bracket

(503) 630 - 7740

- The ColorGard snow retention system dramatically reduces the risks associated with rooftop avalanches
- Mechanically attaches with S-5 Clamps



SKU

ACCS5CG

ASKUS@METALLIONINDUSTRIES.COM

Length

7'-8"

WWW.METALLIONINDUSTRIES.COM



# **ACCESSORIES - CUPOLAS**

SKU



All cupolas are pre-painted 29 gauge steel construction

- Available in over 100 standard colors
- All metal edges are hemmed
- No need to worry about red rust
- Roof and sides interlock for weather tight connection
- Shipped "knock-down", assembles at the job site
- Assembly instructions included
- Premium flashing kit raises the cupola an additional 3-1/2" above the peak of the roof, and gives the sides a fuller look from the ground
- Optional weathervane available in a variety of styles

Size

	Base Style	Length	Width	Louvers	Windows
	Universal	24″	24″	ACCU24UL	ACCU24UW
CURCLAS	Universal	36″	36″	ACCU36UL	ACCU36UW
CUPOLAS	Universal	48″	48″	ACCU48UL	ACCU48UW



- Weathervanes come standard with black finish
- Please contact us for available styles

<u>\$</u>	SKU	Size
	ACWV24S	24″
	ACWV30S	30″
WEATHERVANES	ACWV46S	46″

#### HORSE STALL COMPONENTS

"Your Metal Roofing & Siding Supplier!"

METALLION INDUSTRIES

High quality horse stall systems from CannonBall:HNP.

Suitable for post frame and free standing stall construction.

Available with a variety of horse-safe accessories and components

#### **3100 Series Aluminum Horse Stall Systems**

- Horse stalls of extruded aluminum featuring knocked down construction for easy transport
- Anodized coatings cannot be chewed off like powder coating and provide years of maintenance-free beauty
- Components designed for stall grille heights of either 29" or 36"
- Fast and easy assembly with standard tongue-and-groove dimensional lumber

Additional configurations and product lines available including steel framed.


Please discuss your projects needs with our sales agents.





# HORSE STALL KITS

Hand formed from 16ga. galvanized steel





- Inserts into chuck of 14.4 volt or larger A/C or cordless drill
- Patented adjustable telescoping drill clamp fits width and length of popular drill sizes
- 24ga-30ga capacity in steel panels
- Long-life, dual ball bearings
- 360° rotating head secures in any position for optimum tool clearance and material flow
- Ideal for fast cutting in a wide variety of panel profiles
- Easily installable replacement blades available
- Malco<sup>®</sup> brand Made in USA

	SKU	Description
	TOOTSCM	TurboShear CM
TURBOSHEAR CM	TOOTSCMRB	Replacement Blades



\*Drill Not Included

- Inserts into chuck of 14.4 volt or larger A/C or cordless drill
- Patented adjustable telescoping drill clamp fits width and length of popular drill sizes
- 18ga capacity in steel
- Long-life, dual ball bearings
- 360° rotating head secures in any position for optimum tool clearance and material flow
- Ideal for fast cutting in a wide variety of panel profiles
- *Easily* installable replacement blades available
- Malco<sup>®</sup> brand Made in USA

	SKU	Description
	TOOTSMD	TurboShear - Double Cut
TURBOSHEAR DOUBLE CUT	TOOTSMDRB	Replacement Blades

# **TOOLS - SNIPS**

"Your Metal Roofing & Siding Supplier!"

- Max 2000 series snips with non-slip, serrated jaws
- Hardened alloy steel blades offer maximum edge life
- Steel handle shaft extends through full length of grip
- Extra long life compression spring
- Ergonomic grip
- Malco<sup>®</sup> brand Made in USA



SK	U	Application	Length of Cut	Grip Color		
эм	2001	Cuts Left	1-3/8″	Red		
ЭМ	2002	Cuts Right	1-3/8″	Green		
эм	2003	Cuts Straight, Left & Right	1-11/16"	Yellow	P	REMI



- Length of cut 1-1/4"
- The serrated upper jaw offers solid gripping power with less burr
- Ground tips on jaws allow access in tight areas
- Has the ability to make nickel size blind hole cuts
- Offset cutting plane makes trim cuts both accessible and efficient
- Steel handle shaft extends through full length of grip
- Extra long life compression spring
- Malco<sup>®</sup> brand Made in USA



SKU	Application	Grip Color		
TOOM2006	Cuts Sharp Left Angles, Straight and 5" Circles	Red		
TOOM2007	Cuts Sharp Right Angles, Straight and 5" Circles	Green	PREMIUN	OFFSET AVIAT. SNIPS

- Aviation style steel metal snips
- POWER-FIT performance hand grip
- Convenient self-opening latch quickly opens the snips when ready
- Long-lasting cutting edge



SKU	Application	Length of Cut	Grip Color	
TOOAV6	Cuts Left	1-1/4″	Red	
TOOAV7	Cuts Right	1-1/4″	Green	

AV	ΊΑΤ	101	N SI	NIP



	<b>—</b> A	viation style steel m	netal snips			
6 D	- 9	0-degree angled sni	ps for use in tight s	spaces or ov	erhead	
C. S.	- N	on-slip handle with	cushioned inserts			
	- Lo	ong-lasting forged-s	teel jaws			
		SKU	Application	Length of (	Cut Grip	Color
		TOOAV8	Cuts Left	1-1/4″	F	Red
VERTICAL AVIAT. SNIPS	)	TOOAV9	Cuts Right	1-1/4″	G	reen
				<u>I</u>	<b>I</b>	
		viation style steel m				
		ompact design for ι		vard spaces		
Acres -	- Si	oft, contoured non-	slip grips			
Sig T	- Lo	ong-lasting forged-s	teel jaws			
		SKU	Application	Length of (	Cut Grip	Color
		TOOAVM6EV	Cuts Left	3/4″	F	Red
AVIAT. MINI OFFSET SN	IIPS	TOOAVM7EV	Cuts Right	3/4"	G	reen
			ndlad 10 <sup>11</sup> on in			
		Andy" aluminum ha	ndied 12 snip			
	— Le	ength of cut 3"				
- ar	– Le	ength of cut 3″ ghtweight aluminui	n handle with a sn	-	el	
	– Le	ength of cut 3"	n handle with a sn	-	el	
	- La - Li - Ei	ength of cut 3″ ghtweight aluminui	m handle with a sn gh-carbon steel bla	-	el	
	- La - Li - Ei	ength of cut 3" ghtweight aluminui asily replaceable, hi	m handle with a sn gh-carbon steel bla	ades	el Tool Length	Weight
	- La - Li - Ei	ength of cut 3″ ghtweight aluminur asily replaceable, hi Ialco® brand — Mar	m handle with a sn gh-carbon steel bla de in USA Applicatio Cuts Straight, Le	on ft, Right		Weight 16.7 oz
	- La - Li - Ei	ength of cut 3″ ghtweight aluminur asily replaceable, hi Ialco® brand — Mar SKU	m handle with a sn gh-carbon steel bla de in USA Applicatio Cuts Straight, Le and 6" Circ	on fit, Right	Tool Length	
	- La - Li - Ei	ength of cut 3″ ghtweight aluminur asily replaceable, hi Ialco® brand — Mar SKU	m handle with a sn gh-carbon steel bla de in USA Applicatio Cuts Straight, Le	on fit, Right	Tool Length	
	<ul> <li>Li</li> <li>Ei</li> <li>N</li> </ul>	ength of cut 3" ghtweight aluminur asily replaceable, hi lalco® brand — Mad SKU TOOMC12N TOOULC10	m handle with a sn gh-carbon steel bla de in USA Applicatio Cuts Straight, Le and 6" Circ Cuts Straight, L Right	on fit, Right	Tool Length 12"	16.7 oz
	- Lu - Li - Ei - M	ength of cut 3" ghtweight aluminur asily replaceable, hi lalco® brand — Mae SKU TOOMC12N TOOULC10 ircular "Duckbill" fo	m handle with a sn gh-carbon steel bla de in USA Cuts Straight, Le and 6" Circ Cuts Straight, L Right	ades on eft, Right eft, and	Tool Length 12" 10"	16.7 oz
	<ul> <li>La</li> <li>Li</li> <li>Ei</li> <li>N</li> </ul>	ength of cut 3" ghtweight aluminur asily replaceable, hi lalco® brand — Mar SKU TOOMC12N TOOULC10 ircular "Duckbill" fo laneuvers and cuts	m handle with a sn gh-carbon steel bla de in USA Cuts Straight, Le and 6" Circ Cuts Straight, L Right rged steel snip easily to the very t	ades on eft, Right eft, and ip of the blac	Tool Length 12" 10" de	16.7 oz
	<ul> <li>La</li> <li>Li</li> <li>Ei</li> <li>N</li> </ul>	ength of cut 3" ghtweight aluminur asily replaceable, hi lalco® brand — Mae SKU TOOMC12N TOOULC10 ircular "Duckbill" fo	m handle with a sn gh-carbon steel bla de in USA Cuts Straight, Le and 6" Circ Cuts Straight, L Right rged steel snip easily to the very t	ades on eft, Right eft, and ip of the blac	Tool Length 12" 10" de	16.7 oz
	<ul> <li>La</li> <li>Li</li> <li>Ei</li> <li>N</li> </ul>	ength of cut 3" ghtweight aluminur asily replaceable, hi lalco® brand — Mar SKU TOOMC12N TOOULC10 ircular "Duckbill" fo laneuvers and cuts	m handle with a sn gh-carbon steel bla de in USA Cuts Straight, Le and 6" Circ Cuts Straight, L Right rged steel snip easily to the very t minum, steel sidin	ades on ift, Right cles eft, and ip of the blac g and plastic	Tool Length 12" 10" de	16.7 oz
<image/>	<ul> <li>La</li> <li>Li</li> <li>Ei</li> <li>M</li> <li>C</li> <li>C</li> </ul>	ength of cut 3" ghtweight aluminur asily replaceable, hi lalco® brand — Mad SKU TOOMC12N TOOULC10 ircular "Duckbill" fo laneuvers and cuts uts sheet metal, alu	m handle with a sn gh-carbon steel bla de in USA Cuts Straight, Le and 6" Circ Cuts Straight, L Right rged steel snip easily to the very t minum, steel sidin	ades on ift, Right cles eft, and ip of the blac g and plastic	Tool Length 12" 10" de	16.7 oz
<image/> <section-header><section-header><section-header></section-header></section-header></section-header>	<ul> <li>La</li> <li>Li</li> <li>Ei</li> <li>M</li> <li>C</li> <li>C</li> </ul>	ength of cut 3" ghtweight aluminur asily replaceable, hi lalco® brand — Mad SKU TOOMC12N TOOULC10 ircular "Duckbill" fo laneuvers and cuts uts sheet metal, alu	m handle with a sn gh-carbon steel bla de in USA Cuts Straight, Le and 6" Circ Cuts Straight, L Right rged steel snip easily to the very t minum, steel sidin	ades on ift, Right cles eft, and ip of the black g and plastic atching	Tool Length 12" 10" de	16.7 oz 9.5 oz

(503) 630 - 7740

ASKUS@METALLIONINDUSTRIES.COM

9-3

### **TOOLS - FOLDING & CRIMPING**

"Your Metal Roofing & Siding Supplier!"



- Makes uniform bends along the drip edge of standing seam panels
- High Leverage, Two Post Handle Design
- Rib-Reinforced Steel Plate Construction
- Malco<sup>®</sup> brand Made in USA

SKU	Tool Length	Bending Seam	Bending Capacity
TOODEFT	24″	1" & 1-1/2"	22 ga
TOODEFT1	18″	1" & 1-1/2"	22 ga

- For clean, crisp bends in metal roofing materials
- Quickly adjusts for making bends in a variety of gauges and depths
- Exclusive 3-station roller design produces a uniform bend out to the very ends of a straight panel length
- Center roller station is also independently adjustable for making mildangled bends on a curve
- Hardened rollers assure long service life
- Malco<sup>®</sup> brand Made in USA / Italy



## **DRIP EDGE FOLDING TOOL**



	Capacitie	es in Steel	Bending Depth					
SKU	Min	Max	Min	Max	Weight	2.67		
TOOER3	29 ga	22 ga	5/8″	4″	8.5 lbs	35	TATION EDGE ROLLER	

- Precise Vee-notched depth graduations on jaws are in ¼" increments
- Jaws are drop forged, high impact steel
- Hardened steel handles resist abuse
- Powerful compound leverage design
- Tool also features rust resistant nickel plating
- Non-slip vinyl grips with hand stops provide added comfort and resistance to elements
- Malco<sup>®</sup> brand Made in USA

			L	law		
Sł	۲U	ltem	Depth	Width	Tool Length	Weight
тос	DS3R	3" Offset	1-1/4″	3-1/4″	8″	1.5 lbs
тос	OS2R	3″	1-1/4″	3-1/4″	8-3/4″	1.5 lbs
тос	DS6R	6″	1-1/4″	6″	8-3/4″	1.875 lbs



# HAND SEAMERS

9-4



- Versatile offset jaw design
- Non-marring, vinyl-gripped jaws
- Comfortable vinyl cushioned grips
- Durable cast steel construction for long service life

•	- 1	Malco <sup>®</sup> brand —	Mac	le in USA					
OFFSET SEAMER & TONG	_	SKU	Thro	at Depth	Jaw W	idth	Tool Le	ngth	Weight
OFFSET SEAMER & TONG	S	TOOSG11	1	-1/2″	3-1/	2″	9-1/	2″	3 lbs.
	s ( a F F	Makes quick, eas standing seam ro Can be set to var accommodate a Reinforced steel Removable ergo Contact surfaces	riable wide plate	anel depths of range of p es for dural c handle fo	3/4", 1", anel rib h pility pr ease of	1-1/4", eights use and	and 1-1/	2" to prage	
	9	scratching							
DI PAN FOLDING TOOL				SKU		Widt			Max. Ga.
				TOOFOL	DDI	18″			22
	(	Designed for use other application Constructed of h	าร			out ma	y be usec	l for ma	any
		SKU		Profile			Rib	Spacing	
		TOOCRIMPL12	2	12" Loc Seam				12″	
		TOOCRIMPL16	•	16" Loc Seam				16″	
PANEL CRIMP TOOLS		TOOCRIMPM		Magn	a Rib, Del	ta Rib I	l & III	8	" or 9"
	TOOCRIMPM       Magna Rib, Delta Rib II & III       8" or 9         Image: Composition of the state								
C C C C C C C C C C C C C C C C C C C	- 6	Ergonomic Redli	ne Ha	produces 7 andles won	to 1 mecl			ge	
DOWNSPOUT CRIMPER	- 6	Ergonomic Redli	ne Ha	oroduces 7 andles won le in USA	to 1 mecl			ge Weig	ht

# **TOOLS - SAW BLADES**

"Your Metal Roofing & Siding Supplier!"

- Saws through metals quickly and accurately leaving clean, burr-free cuts behind
- Ideal for cutting steel studs, pipe, and sheets for most mild steels under 1/4"
- Durable Triple Chip Grind (TCG) metal cutting tooth design maximizes cutting life and speed
- Laser cut stabilizer vents trap noise and vibration—keeping it cool
- Freud<sup>®</sup> brand Made in Italy



SKU	Dia.	Teeth	Arbor	Material Usage	
TOOD0748CFA	7-1/4″	48	5/8″	Steel	
TOOD0648CFA	6-1/2″	48	5/8″	Steel	
TOOD0624A	6-1/2″	24	5/8″	Wood	
TOOD0660A	6-1/2″	60	5/8″	Wood	

# **CIRCULAR SAW BLADES**

- High speed steel cutting edge welded to a flexible high carbon steel back
- Superior manufacturing process outperforms all others
- Malco<sup>®</sup> brand Made in Switzerland

SKU	Length	Application
TOO3MC24	4″	Cuts sheet metal, pipe, and profiles up to 18 ga
TOO4TF14	6″	Cuts all metals including stainless steel over 1/8"



# **RECIPROCATING BLADES**

**METALLION INDUSTRIES** "Your Metal Roofing & Siding Supplier!"

# **TOOLS - PUNCHES & NOTCHERS**

		urable steel c	onstruction otching of trim		c Seam panel profiles iring cutouts to accommo-
		SKU	Pan	el Profile	Panel Max. Ga.
LOC SEAM PANEL N		TOONOT	ICHL Lo	c Seam	24
LOC SEAIVI PAINEL IN	NOTCHER	τοονοτά	CHLPD	Replace	ment Punch & Die Set
	- Re	eplaceable pu djustable thro	d maneuverab unch and die in pat depth for e lline handles w	stalls on the j asy hole plac	ement
				Throat D	Depth
	SKU		Min.		Max.
			iviiii.		Widx.
HOLE PUNCH	TOOHP18KF TOOHPD18		1/2″	eplacement	1-1/8" Punch & Die Set
HOLE PUNCH	TOOHPD18	unches raise a	1/2" 1/8" R a shaped projec		1-1/8" Punch & Die Set netal edges for quickly
HOLE PUNCH	TOOHPD18	Inches raise a cking metal f	1/2" 1/8" R a shaped projec inish trim Descript	ction along m	1-1/8" Punch & Die Set netal edges for quickly Usage
HOLE PUNCH	TOOHPD18	unches raise a	1/2" 1/8" R a shaped projec inish trim Descript Snap Lock I	ion Punch	1-1/8" Punch & Die Set netal edges for quickly Usage Heavy Duty
	TOOHPD18	Inches raise a cking metal f KU DSL1R OSL5 Unches a gene ongating nail gonomic Red esigned for o	1/2" 1/8" R a shaped projec inish trim Descript Snap Lock Sing	ion Punch Jle Punch /4" horizonta les on't wear yo	1-1/8"         Punch & Die Set         hetal edges for quickly         Usage         Heavy Duty         Light Duty         al slot for adding or         u down
	TOOHPD18	Inches raise a cking metal f KU DSL1R OSL5 Inches a gene ongating nail gonomic Red	1/2" 1/8" R a shaped projection inish trim Descript Snap Lock Sing erous 5/32" x 3 or fastener ho lline handles w ne handed ope	ion Punch Jle Punch /4" horizonta les on't wear yo ration	1-1/8"         Punch & Die Set         hetal edges for quickly         Usage         Heavy Duty         Light Duty         al slot for adding or

(503) 630 - 7740

ASKUS@METALLIONINDUSTRIES.COM

WWW.METALLIONINDUSTRIES.COM

9-7

# **TOOLS - DRIVERS**



- Cleanable & Reversible
- Two drivers in one (1/4" & 5/16")
- 2" Length
- Designed to work effectively with painted fasteners



SKU	Sizes	
OOMSHC2	1/4" & 5/16"	REVERSIBLE MAGNETIC HEX DRIVER
<ul> <li>Resists im</li> </ul>	pact driver stress	
Fail-proof	engagement of faste	ner head
	aded floating magnet	
SKU	Sizes	
OMSHL14IS	1/4"	IMPACT GRADE MAGNETIC HEX DRIVER
	1	
Designed	with painted screw h	eads in mind, reducing the risk of
		eads in mind, reducing the risk of
marring t	ne paint	
marring t		
marring the state of the state	he paint versized with rounded	d corners
marring the state of the state	ne paint	d corners
marring ti Slightly ov Also work	he paint versized with rounded great with unpainted	d corners
marring ti Slightly ov Also work SKU	he paint versized with rounded great with unpainted Sizes	d corners d screws
marring ti Slightly ov Also work SKU	he paint versized with rounded great with unpainted	d corners
marring ti Slightly ov Also work SKU	he paint versized with rounded great with unpainted Sizes	d corners d screws
marring ti Slightly ov Also work	he paint versized with rounded great with unpainted Sizes	d corners d screws
marring ti Slightly ov Also work SKU	he paint versized with rounded great with unpainted Sizes	d corners d screws
marring ti Slightly ov Also work SKU TOOND3/8	he paint versized with rounded great with unpainted Sizes	d corners d screws MAGNETIC HEX DRIVER
marring ti Slightly ov Also work SKU TOOND3/8 #2 square	he paint versized with rounded great with unpainted Sizes 3/8" drive, 1-15/16" overa	all length
marring ti Slightly ov Also work SKU TOOND3/8 #2 square	he paint versized with rounded great with unpainted Sizes 3/8" drive, 1-15/16" overa	d corners d screws MAGNETIC HEX DRIVER
marring ti Slightly ov Also work SKU TOOND3/8 #2 square	he paint versized with rounded great with unpainted Sizes 3/8" drive, 1-15/16" overa	all length
marring ti Slightly ov Also work SKU TOOND3/8 #2 square	he paint versized with rounded great with unpainted Sizes 3/8" drive, 1-15/16" overa	all length





## **DOUBLE ENDED SHEET METAL BITS**

SKU	Sizes	Twist Length	Qty.
TOODE30B	2″	1/2″	1
TOODE30	2″	1/2″	12

- Double flute design assures penetration of soft and thin materials
- Drill holes without burring or deforming stock
- Perfect for use as a "hole-opening" reamer
- Can be resharpened

		Hole	e Diameter	
	SKU	Min.	Max.	Increments
STEP DRILL BIT	TOOUB3	1/4″	3/4″	1/16″



· ·····

- SDS Hammer Drill Bits
  - Use with our concrete anchor product lines

SKU	Dia.	Overall Length	Max. Drill Depth
TOOSDS144	1/4″	4″	2″
TOOSDS126D	1/2″	6″	4″
TOOSDS128D	1/2″	8″	6″
TOOSDS588D	5/8″	8″	6″

### **TOOLS - CORDLESS (MAKITA)**

"Your Metal Roofing & Siding Supplier!"

METALLION INDUSTRIES

the 18V LXT® Brushless 2-Piece Combo Kit (model XT291M) gives you two brushless solutions for drilling, driving and fastening. Each tool features an efficient Makita BL™ Brushless Motor that is electronically controlled for longer run time, increased power and speed, and longer tool life.

#### Kit Includes:

- 18V LXT<sup>®</sup> Brushless 1/2" Hammer Driver-Drill (XPH14Z)
- 18V LXT<sup>®</sup> Brushless Impact Driver (XDT13Z)
- 18V LXT<sup>®</sup> Lithium-Ion Rapid Optimum Charger (DC18RC)
- 2 x 18V LXT<sup>®</sup> Lithium-Ion 4.0Ah Battery (BL1840B)
- Tool Bag

SKU

TOOEMACOMDID

#### Makita 18V Hammerdrill & Impact Driver Combo Kit

The 18V LXT<sup>®</sup> Brushless 1/2" Driver-Drill is an ideal premium drilling and driving solution.

- Delivers 1,250 in.lbs. of Max Torque.
- 2-speed transmission (0-550 and 0-2,100 RPM) for a wide range of drilling and fastening applications
- All-metal 1/2" self-ratcheting chuck provides improved bit gripping strength and durability



		Battery			
SKU	Model	Incl.	Volt.	Cap.	Makita 18V 1/2" Drill/Driver
TOOEMADR	XFD14Z	NO	18V		Makita Tov 1/2 Dilli/Dilver

The Makita 18V LXT<sup>®</sup> Lithium-Ion Brushless Cordless Quick-Shift Mode<sup>™</sup> 3-Speed Impact Driver is a best-in-class fastening solution for users who want more torque, longer run-time, and precision fastening features

- BL<sup>™</sup> Brushless Motor delivers 3,600 Max RPM and 1,550 in.lbs. of Max Torque
- 3-speed power selection switch (0-1,100 / 0-2,100 / 0-3,600 RPM & 0-1,100 / 0-2,600 / 0-3,800 IPM) provides precise fastening control for a wide range of applications



			Battery		
SKU	Model	Incl.	Volt.	Cap.	Makita 18V 3-Speed Imapct Driver
TOOEMAID	XDT14Z	NO	18V		Makita 188 3-Speed Imapct Driver



# **TOOLS - CORDLESS (MAKITA)**



- 18V LXT® Lithium-Ion Brushless Cordless 6-1/2" Circular Saw
- Powerful Makita-built electronically controlled brushless motor delivers 5,000 RPM for faster cutting and ripping
- Automatic Speed Change<sup>™</sup> technology adjusts cutting speed and torque during cut for optimum performance
- Brushless motor is electronically controlled to optimize battery energy use for up to 50% longer run time per charge

					Battery	
Makita 18V 6-1/2″ Circu	lon Cour	SKU	Model	Incl.	Volt.	Cap.
IAKITA TOV 0-1/2 CIFCU	lar Saw	TOOEMACS	XSH03Z	NO	18V	
	18V LXT Brush	less Cordless Offset	Shear (18 Gau	ge)		
et.	Cuts up to	18 ga. mild steel, 20	) ga. stainless s	teel and c	apable of	
2 0 Thakita	radius cut	s up to 3" in various	sheet metal ty	bes		
		less motor is design		r and moi	e efficiently	,
	_	life; delivers variable				
02		le steel blades with erial thickness	a maximum cut	: capacity	of up to Battery	
	10 gu. mu	SKU	Model	Incl.	Volt.	Сар
akita 18V Offset 18ga.	Shears	TOOEMAOS	XSJ04Z	NO	18V	
	10) ( L) (T @ D	hless Cordless Strai				
	for longer Replaceab	less motor is design life; delivers variable le steel blades with al thickness	e 0-3,000 SPM a maximum cu	capacity	of up to 14 Battery	
lakita 18V 14ga. Doubl	e Cut Shears	SKU	Model	Incl.	Volt.	Cap
kitu lov ligu boubi		TOOEMADS	XSJ03Z	NO	18V	
	18V LXT <sup>®</sup> Lithi	um-Ion Cordless 16	Gauge Nibbler	(16 Gauge	e)	
	Ideal for c	utting roofing sheet	metal at thickn	esses up 1	to 16 gauge	
	<ul> <li>Cutting rad</li> </ul>	dius: inner edge 1-3/	4"; outer edge	2″		
Ŧ	- Makita-bu	ilt motor delivers 1,9	900 SPM for fas	ster and si	mooth	
(L)	cutting				Battery	
akita 181/ 16ga Nibble	ar	SKU	Model	Incl.	Volt.	Сар
Makita 18V 16ga. Nibble	er	SKU TOOEMANIB		Incl. NO	Volt.18V	Сај

"Your Metal Roofing & Siding Supplier!"



The Rapid Optimum Charger offers key advantages for Makita 18V Lithium-Ion cordless tool users. The exclusive built-in fan cools the battery by forcing air through the battery's air vents during the charging process for faster charging.



		Battery				
	Cap.	Volt.	Incl.	Model	SKU	
kita 14.4V / 18V Charger		14.4V/18V	NO	DC18RC	TOOEMABC	

18V LXT Lithium-Ion 5Ah Battery

- The Makita 18V LXT<sup>®</sup> Lithium-Ion battery charges faster and works longer than standard lithium-ion batteries
- The Makita 5.0Ah battery has a category-leading charge time of only 45 minutes
- Compatible only with Star Protection tools, indicated by the Star Symbol<sup>™</sup> and/or Yellow Battery Receiver under the tool

		Battery			
SKU	Model	Incl.	Volt.	Cap.	
TOOEMAB51	BL1850B	1	18V	5.0Ah	
TOOEMAB52	BL1850B-2	2	18V	5.0Ah	



Makita 18V LXT 5Ah Battery

18V LXT Lithium-Ion 3Ah Battery

- The Makita 18V LXT<sup>®</sup> Lithium-Ion battery charges faster and works longer than standard lithium-ion batteries
- The Makita 3.0Ah battery has a category-leading charge time of only 30 minutes
- Compatible only with Star Protection tools, indicated by the Star Symbol<sup>™</sup> and/or Yellow Battery Receiver under the tool

		Battery				
SKU	Model	Incl.	Volt.	Cap.		
TOOEMAB31	BL1830B	1	18V	3.0Ah		
TOOEMAB32	BL1830B-2	2	18V	3.0Ah		



# Makita 18V LXT 3Ah Battery

9-12



# **TOOLS - CORDLESS (DEWALT)**



Expand your system and Experience Power<sup>™</sup> with lightweight 20V MAX\* XR<sup>®</sup> tools ideal for tough fastening, drilling, and hammering applications.

#### Kit Includes:

- 20V MAX XR Cordless Brushless Hammer Drill (DCD996)
- 20V MAX 1/4" Impact Driver (DCF887)
- 2 x 20V MAX 5Ah Batteries
- Battery Charger
- Durable Storage Bag

#### DeWalt 20V Hammerdrill & Impact Driver Combo Kit

SKU TOOEDECOMDID



Experience Power<sup>™</sup> and complete a wide range of heavy-duty fastening applications with the 20V MAX\* XR<sup>®</sup> Brushless 1/2 in. Drill/Driver. Engineered for advanced performance, this versatile drill delivers up to 2,000 rpm when drilling into wood and metal.

- High-speed transmission with variable trigger and 2 speed settings (0-650/0-2,000 rpm)
- Adjustable 3-Position, 3 Mode LED with up to 70 Lumens, including LED spotlight mode which features a 20-minute shutoff function for extended work time in low-light spaces

				Battery	
DeWalt 20V 1/2" Drill/Driver	SKU	Model	Incl.	Volt.	Cap.
Devvalt 200 1/2 Drill/Driver	TOOEDEDR	DCD800B	NO	20V	



Experience Power<sup>™</sup> and complete tough jobs in tight spaces with this 20V MAX\* XR<sup>®</sup> 3-Speed 1/4 in. Impact Driver. Featuring a compact design and 3-speeds, this powerful impact driver delivers premium user control for a variety of applications.

 3 LEDs with 20-second delay after trigger release, provide visibility without shadows

One-handed loading 1/4" hex chuck with easy grip sleeve, accepts
 1" bit tips

				Battery	
	SKU	Model	Incl.	Volt.	Cap.
DeWalt 20V 1/4" Impact Driver	TOOEDEID	DCF887B	NO	20V	
					10
(503) 630 - 7740 📕 ASKUS@METALLIONINDUSTRIES.COM	WWW.METALI	IONINDUSTRIES.	сом	9	-13

### **TOOLS - CORDLESS (DEWALT)**

"Your Metal Roofing & Siding Supplier!"



Combining performance and versatility, the 20V MAX\* 6-1/2 in. Cordless Circular Saw is ready to take on a variety of cutting applications. It features a powerful brushless motor that delivers 4,950 rpm for fast, accurate, and consistent cutting

- Tool-free depth and bevel adjustments provide a max depth of cut of 2-1/8 in. at 90° along with a max bevel of 50°
- This saw is equipped with a built-in rafter hook & bright LED



Cap.	
	DeWalt 20V 6-1/2" Circular Saw

20V MAX\* Swivel Head Offset Cordless Shears (18 Gauge)

- Tool-free 360 swivel head which allows user to access tight quarters while maintaining comfort
- Offset shear design can easily turn and cut circles.
- LED work light illuminates surface.




				Battery		
	SKU	Model	Incl.	Volt.	Cap.	
ſ	TOOEDEOS	DCS496B	NO	20V		DeWalt 20V Offset 18ga. Shears

20V MAX\* Swivel Head Double Cut Cordless Shears (14 Gauge)

- Tool-free 360 swivel head which allows user to access tight quarters while maintaining comfort
- Cuts 7/32" strip which continuously curls out of the cutting area providing consistent and accurate cuts.
- LED work light illuminates surface.



			Battery		
SKU	Model	Incl.	Volt.	Cap.	
TOOEDEDS	DCS494B	NO	20V		DeWalt 20V 14ga. Double Cut Shears
9-14	(50:	3) 630 - 7	7740	ASKUS	@METALLIONINDUSTRIES.COM WWW.METALLIONINDUSTRIES.COM



# **TOOLS - CORDLESS (DEWALT)**



Charge your 12V MAX\* and 20V MAX\* batteries in 90 minutes or less with this 12V/20V MAX\* Battery Charger that is designed to minimize downtime.

				Battery	
	SKU	Model	Incl.	Volt.	Cap.
DeWalt 12V / 20V MAX Charger	TOOEDEBC	DCB115	NO	12V/20V	



20V MAX\* XR<sup>®</sup> 5Ah Battery (2 Pack)

- Premium XR<sup>®</sup> Lithium Ion pack provides up to 60% more capacity than standard 20V MAX\* battery pack
- 3-LED fuel gauge system allows immediate feedback on state of charge
- No memory and virtually no self-discharge for maximum productivity and less downtime

					Battery	
DeWalt 20V MAX XR 5Ah Battery		SKU	Model	Incl.	Volt.	Cap.
		TOOEDEB52	DCB205-2	2	20V	5.0Ah



20V MAX\* Compact 2Ah Battery (2 Pack)

- Compact Lithium Ion pack provides up to 33% longer run-time than standard 20V MAX\* battery packs
- 3-LED fuel gauge system allows immediate feedback on state of charge
- No memory and virtually no self-discharge for maximum productivity and less downtime

					Battery	
		SKU	Model	Incl.	Volt.	Cap.
DeWalt 20V MAX Compact 2Ah Battery		TOOEDEB22	DCB203-2	2	20V	2.0Ah

# **TOOLS - CORDLESS (MILWAUKEE)**

"Your Metal Roofing & Siding Supplier!"



Our M18 FUEL 2-Tool Combo Kit has the Most Powerful Drill, including AutoStop<sup>™</sup> Control Mode for enhanced safety and the Fastest Driving Impact Driver.

#### **Kit Includes:**

- M18 FUEL 1/2" Hammer Drill /Driver (2904-20)
- M18 FUEL 1/4" Hex Impact Driver (2953-20)
- Z x M18 REDLITHIUM<sup>™</sup> XC 5.0Ah Battery Pack (48-11-1850)
- M18/M12 multi-voltage charger and carrying case (48-59-1812)
- Case, belt clips, and side handle

#### SKU TOOEMICOMDID

### Milw. M18 1/2" Drill/Driver & 1/4" Impact Driver Combo Kit

Our M18 FUEL<sup>™</sup> ½" Drill Driver is the Industry's Most Powerful Drill, Most Compact solution in class and features AutoStop<sup>™</sup> Control Mode for Enhanced Safety.

- 1400 in-lbs of torque
- POWERSTATE<sup>™</sup> Brushless Motor delivers the power to complete the widest range of applications of any drill driver
- 1/2" all-metal chuck with carbide teeth for maximum durability, grip and bit retention



				Battery				
	SKU	Model	Incl.	Volt.	Cap.	N/:	lw. M18 1/2" Drill/Driver	
ľ	TOOEMIDR	2903-20	NO	18V			Iw. M16 1/2 Drill/Driver	

The M18 FUEL<sup>™</sup> SURGE<sup>™</sup> 1/4" Hex Hydraulic Driver is the quietest cordless fastening solution on the market .

- POWERSTATE™ Brushless Motor delivers up to 3,000 RPM
- With Milwaukee's new FLUID-DRIVE<sup>™</sup> Hydraulic Powertrain, users will experience up to 50% quieter operation, 3X less vibration for smoother operation, and faster driving speeds compared to standard impacts.
- 4-Mode DRIVE CONTROL<sup>™</sup> provides greater control over output speed and power for greater versatility



			Battery		
SKU	Model	Incl.	Volt.	Cap.	Milw. M18 1/4" Hex Driver
TOOEMIID	2760-20	NO	18V		Milw. W18 174 Hex Driver
0.40					
9-16	(503) 6	30 - 7740	) 📕 Δ9	SKUS@MET	ALLIONINDUSTRIES.COM WWW.METALLIONINDUSTRIES.COM



ASKUS@METALLIONINDUSTRIES.COM



#### M18 FUEL™ 6-1/2" Circular Saw

- POWERSTATE™ Brushless Motor: Outpowers all other 18-volt cordless circular saws and provides up to 3X longer tool life
  - REDLITHIUM<sup>™</sup> XC5.0 Battery Pack: Offers up to 4X more runtime, 20% more power and up to 2X more recharges than competitive batteries
  - REDLINK PLUS<sup>™</sup> Intelligence: The most advanced electronic system on the market maximizes performance

				Battery	
	SKU	Model	Incl.	Volt.	Cap.
Milw. M18 6-1/2" Circular Saw	TOOEMICS	2730-20	NO	18V	

M18 Single Cut Offset Shear (18 Gauge)

- Steel capacity: 18-Gauge
- Stainless steel capacity: 20-Gauge
- Compatible with all M18<sup>™</sup> batteries and M18<sup>™</sup> chargers
- Variable Speed Trigger

				Battery	
	SKU	Model	Incl.	Volt.	Cap.
Milw. M18 Offset 18ga. Shears	TOOEMIOS	2637-20	NO	18V	



M18 Double Cut Shear (18 Gauge)

- Steel capacity: 18-Gauge
- Stainless steel capacity: 20-Gauge
- Compatible with all M18<sup>™</sup> batteries and M18<sup>™</sup> chargers
- Variable Speed Trigger

				Battery	
	SKU	Model	Incl.	Volt.	Cap.
Milw. M18 18ga. Double Cut Shears	TOOEMIDS	2635-20	NO	18V	

# TOOLS - CORDLESS (MILWAUKEE)

"Your Metal Roofing & Siding Supplier!"



M12 FUEL Variable Speed Nibbler (16 Gauge)

- Fast, Clean Cuts in 16GA Mild Steel Up to 7 Feet per Minute
- Power to Cut 18GA Stainless and 12GA Aluminum
- Power to Cut 22GA Spiral Duct Seams
- Chip Collection Bag Included for Easy Clean Up
- M12 REDLITHIUM<sup>™</sup> Battery Technology



			Battery			
SKU	Model	Incl.	Volt.	Cap.		
TOOEMINIBM12	2476-20	NO	12V		Milw. M12 16ga. Nibbler	

M18 Cordless 10oz. Caulk and Adhesive Gun

- All-metal gears: Deliver industry-leading 950 lbs of dispensing force for the highest viscosity materials
- CFT<sup>™</sup> Constant Flow Technology: Offers steady flow rate and even beads at all viscosity levels
- Anti-drip mechanism: Instantly stops material from dripping upon trigger release
- Conversion kit available for compatibility with 20 oz. sausage style material packs

		Battery				
	Cap.	Volt.	Incl.	Model	SKU	
		18V	NO	2641-20	TOOEMICG	
Milw. M18 10oz Caulk Gun	sion Kit	ack Conver	ge Style P	20 oz. Sausa	TOOEMISCK	

#### M12 Rivet tool

- 450 1/8" Steel Rivets per charge
- Pull 3/32", 1/8", 5/32", 3/16" Rivets
- Aluminum, Steel, Stainless Steel Capacity
- 2,000 lbs. pulls force
- Tool holds rivet in any orientation

		Battery			
SKU	Model	Incl.	Volt.	Cap.	Miles M42 Direct our
TOOEMIRGM12	2550-20	NO	12V		Milw. M12 Rivet gun
0.40			• •	- -	
9-18	(503) 630 - 7	740	ASKUS	METALLIC	NINDUSTRIES.COM WWW.METALLIONINDUSTRIES.COM



# **TOOLS - CORDLESS (MILWAUKEE)**



Always be ready for your next job with this cross-system charger. The M18<sup>™</sup> & M12<sup>™</sup> Multi-Voltage Charger accepts all M18<sup>™</sup> and M12<sup>™</sup> batteries, so you'll always be prepared and productive, especially on jobs that require a mix of M12 and M18 Milwaukee cordless power tools.

				Duttery	
	SKU	Model	Incl.	Volt.	Cap.
Milw. M12 / M18 Charger	TOOEMIBC	48-59-1812	NO	12V/18V	

M18<sup>™</sup> REDLITHIUM<sup>™</sup> XC5.0 Extended Capacity Battery



■ REDLINK<sup>™</sup> Intelligence: Provides optimized performance and overload protection using total system communication between tool, battery and charger

✓ Versatility: Powers more than 60 Milwaukee® M18<sup>™</sup> cordless power tools

			SKU	Model	Incl.	Volt.	Cap.	
		TOOEMIB5M181	48-11-1850	1	18V	5.0Ah		
	Milw. M18 Redlithium XC 5Ah Battery		TOOEMIB5M182	48-11-1852	2	18V	5.0Ah	

#### M18<sup>™</sup> REDLITHIUM<sup>™</sup> HIGH OUTPUT<sup>™</sup> CP3.0 Battery

■ REDLINK<sup>™</sup> Intelligence: Our battery circuitry provides optimized performance and overload protection using total system communication between tool, battery and charger

Compatible with all M18<sup>™</sup> tools

	<ul> <li>2 year battery warranty</li> </ul>				Battery			
		SKU	Model	Incl.	Volt.	Cap.		
Milw. M18 Redlithium HO 3Ah Battery		TOOEMIB3M181	48-11-1835	1	18V	3.0Ah		
		TOOEMIB3M182	48-11-1837	2	18V	3.0Ah		



M12<sup>™</sup> REDLITHIUM<sup>™</sup> CP2.0 Compact Battery

■ REDLINK<sup>™</sup> Intelligence: Provides optimized performance and overload protection using total system communication between tool, battery and charger

✓ Versatility: Powers all Milwaukee M12<sup>™</sup> cordless power tools

						Battery	
Milue M12 Padlithium 24		SKU	Model	Incl.	Volt.	Cap.	
Milw. M12 Redlithium 24	In Dattery		TOOEMIB2M121	48-11-2420	1	12V	2.0Ah
(503) 630 - 7740 📕 ASKUS@METALLION	ASKUS@METALLIONINDUSTRIES.COM			WWW.METALLIONINDUSTRIES.COM			-19

### **TOOLS - MISCELLANEOUS**



- 11/16" BiMetal Hole Saw
- No separate arbor required
- High speed steel
- Shatterproof



SKU	Cutting Dia.	Max. Depth	
TOOH11	11/16″	1.75″	HOLE-IN-ONE SAW
TOOHSB	1/4″ Pilo	ot Bit	HOLE-IN-ONE SAW

- Flexible lightweight design for easy use
- Compact design
- Puncture wire included
- Ladder size hang hook



SKU	Capacity	Carriage Diameter	Tool Length	FLEXIBLE CAULK GUN
TOOCG12	1/10 gal	2″	13.4″	TELAIDEE CAOER GOIN

- Heavy-duty professional model with thumb activated pressure release
- Designed for use with a spouted cartridge
- Powerful ratcheting action minimizes worker fatigue or need to warm caulk up
- User can regulate stroke to fit hand; plus rod may be rotated
- Hand puncture wire folds inside handle
- Malco<sup>®</sup> brand Made in Taiwan



SKU	Capacity	Carriage Diameter	Tool Length	HEAVY DUTY CAULK GUN	
TOOCG20	1/10 gal	2″	14″	HEAVE DOTT CAULK GUN	



# **TOOLS - MISCELLANEOUS**



- Lightweight design capable of withstanding shock and abuse
- Precision cast parallel edges will not scratch work surfaces
- Three large vials plumb, level and 45°
- White vial holders and top read feature facilitate quick, easy reading
- A grooved working edge design is ideal for use on pipe and conduit

				SKU	Length
MAGNETIC TORPEDO				TOOL9M	9″
		tile for a variati	of motol work		
		atile for a variet			
Holes and Company of the State	- Long	lasting cutter bi	t		
	Preci	sion-fit sealed b	earings		
	Easy-	-adjusting pivot	pin		
T	🗕 Repla	acement cutting	bits available		
				Hole Di	ameter
		SKU	Description	Min.	Max.
HOLE CUTTER		TOOHC1	Hole Cutter	2″	12″
HOLE COTTER		ТООСВ	Replacem	ent Cutting Bit	-
	- Abra	sion-resistant n			
	- Abra		lon coating	ane	
	- Abra	sion-resistant nu	lon coating	ape Lenc	ıth
	<ul><li>Abra:</li><li>Rubb</li></ul>	sion-resistant n	lon coating	ape Leng 16	
MAGNETIC TIP TAPE	- Abra Rubb	sion-resistant ny per-clad housing SKU	/lon coating T Width	Leng	,
MAGNETIC TIP TAPE	Abra: Rubb	sion-resistant mo per-clad housing SKU T416M T430M	/lon coating Ta Width 1" 1"	Leng 16	,
•	Abra: Rubb	sion-resistant ny per-clad housing SKU T416M	/lon coating Ta Width 1" 1"	Leng 16	,
•	Abra: Rubb	sion-resistant mo per-clad housing SKU T416M T430M	vlon coating Tr Width 1" 1"	Leng 16	,
	<ul> <li>Abra:</li> <li>Rubb</li> <li>Rubb</li> <li>Easy</li> <li>Complete</li> </ul>	sion-resistant mo per-clad housing SKU T416M T430M one handed use pact & lightweig	vlon coating Tr Width 1" 1"	Leng 16 30	,
<image/> <section-header><section-header></section-header></section-header>	<ul> <li>Abra:</li> <li>Rubb</li> <li>Rubb</li> <li>Easy</li> <li>Comp</li> <li>Supp</li> </ul>	sion-resistant mo per-clad housing SKU T416M T430M one handed use pact & lightweig	Vion coating Tr Width 1" 1" ht eces for 2.4, 3.0/3.2, and	Leng 16 30	,
Contraction of the second seco	<ul> <li>Abra:</li> <li>Rubb</li> <li>Rubb</li> <li>Easy</li> <li>Comp</li> <li>Supp</li> </ul>	sion-resistant mo per-clad housing SKU T416M T430M one handed use pact & lightweig lied with nosepi	Vion coating Tr Width 1" 1" ht eces for 2.4, 3.0/3.2, and	Leng 16 30	,
•	<ul> <li>Abra:</li> <li>Rubb</li> <li>Rubb</li> <li>Easy</li> <li>Comp</li> <li>Supp</li> </ul>	sion-resistant mo per-clad housing SKU T416M T430M one handed use pact & lightweig lied with nosepi	Vion coating Tr Width 1" 1" ht eces for 2.4, 3.0/3.2, and	Leng 16 30	, ,

9-21

### **TOOLS - MISCELLANEOUS**

"Your Metal Roofing & Siding Supplier!"

- Easily transport, organize, and protect your tools
- 1690D ballistic nylon shell and pockets, with bonded double stitching
- 33 duo-colored pockets and pouches make it easy to organize and find tools
- External storage includes two expandable side-pockets plus padded and zippered pockets for tablets, laptops, and cell phones
- Comfortable, wide padded shoulder straps
- Large, single, top-mounted handle for ease of carrying



SKU	Description	
TOOL9M	Tool Backpack	

- Use with G-Type (Heavy Duty) staples
- Carbon fiber structure for less weight and exertion
- 500k strike cycles
- Drop in loading for easy reloading of fasteners
- Hammer style grip for comfort and ease of use
- Auto-lock, anti-jam pinch latch for reliable operation

(503) 630 - 7740

- Vibration absorbing grip
- Use with our 3/8" chisel point staples (FST38)



	es	Staple Siz			SKU
HAMMER TACKER	1/2″	3/8″	5/16"	ALT	TOOHTDEWA
DASCO PRO Salesta Est		and scrap	reated hig n tight spa s, pulling, a	or use in or prying,	<ul><li>Great for</li><li>Ideal for</li></ul>
PRY SCRAPER		ngth	lth Lei	Wid	SKU
		10″	/4″ 1	1-3/	TOOPRY

ASKUS@METALLIONINDUSTRIES.COM

WWW.METALLIONINDUSTRIES.COM





- TenActiv gloves offer a superior combination of dexterity and cut resistance
- G-Tek gloves are optimized for extreme hand protection and comfort
- Both brands of glove offer touchscreen usability

	SKU	Description	Coating	Size
	TOOGLSUPS	Superior TenActiv	Foam Nitrile	Small
	TOOGLSUPM	Superior TenActiv	Foam Nitrile	Medium
	TOOGLSUPL	Superior TenActiv	Foam Nitrile	Large
	TOOGLSUPXL	Superior TenActiv	Foam Nitrile	X-Large
GLOVES	TOOGLSUPM-EXT	Extreme Cut Superior TenActiv	Foam Nitrile	Medium
GLOVES	TOOGLSUPM-X7EXT	Extreme Cut PIP G-Tek PolyKor X7	NeoFoam	Medium

- Korkers TuffTrax 3-in-1 overshoe
- Provides traction on smooth, wet surfaces like metal roofs and tile
- Quick release, replaceable buckle & strap system for easy on/off
- Molded rubber walls at toe, heel and side provide a secure fit
- Overshoe purchase includes one pair of replaceable metal roofing foam soles

	SKU	Description	Application	Size
*Boot Not Included	TOOKORTTMD TuffTrax Overshoe			Medium
	TOOKORTTLG	TuffTrax Overshoe		Large
	TOOKORSOMDMET	Replacement Soles (Pair)	Metal Roofing	Medium
	TOOKORSOLGMET	Replacement Soles (Pair)	Metal Roofing	Large
OVERSHOE	TOOKORSOMDCOM	Replacement Soles (Pair)	Composition Roofing	Medium
OVERSHOE	TOOKORSOLGCOM	Replacement Soles (Pair)	Composition Roofing	Large

- Strap comes equipped with versatile J-hook ratchet, which allows you to hook the strap back to itself using the floating D-ring
  - Corner protector designed with raised edges to keep it in place. Accommodates webbing widths up to 4"

	SKU	Description	Width	Length
	TOORS1	Nylon Ratchet Strap	1″	15′
RATCHET STRAPS	TOOCPP Plastic Corner Protecto		4"	4-7/8″
		<u>.</u>		

# **TOOLS - RENTAL EQUIPMENT**

"Your Metal Roofing & Siding Supplier!"



- Portable hand crimpers for use with our mechanically seamed panel profiles
- Durable steel construction
- Ergonomic handles allow ease of use

			Crim	р	
	SKU	Panel	Width	Length	Panel Max. Ga.
I	RCRIMP1-90	MI-150	90°	6″	22
	RCRIMP2-90	MI-210	90°	6″	22
R	CRIMP2-180	MI-210	90° & 180°	4″	22

- Portable mechanical seamers for use with our mechanically seamed panel profiles
- Auto-shutoff safety switch
- Extension cord rentals available

				Panel Gauge		Po	wer	
	SKU	Panel	Seam	Min.	Max.	Amps	Volts	Weight
	RSEAMM1-90	MI-150	90°	26	24	7	120	35 lbs
	RSEAMM2-90	MI-210	90°	24	22	11.5	110	89 lbs
R	RSEAMM2-180	MI-210	180°	24	22	11.5	110	89 lbs
R	SEAMM275-90	MI-275	90°	24	22	11.5	110	89 lbs



**MECH. SEAM CRIMPERS** 

# **MECHANICAL SEAMERS**

- Ideal for shearing to length and gable end cuts
- Available in straight or adjustable angle cut models
- For use with our Magna Rib and PBR panel profiles
- Angle cut models max angle 18.43° (4:12 pitch)

	Panel			
SKU	Profile	Max. Ga.	Cut	
RSHEARMS	Magna Rib	24	Straight	
RSHEARMA	Magna Rib	Magna Rib 24		
RSHEARPS	PBR	24	Straight	
RSHEARPA	PBR	24	Angle	



# **PORTABLE SHEARS**

#### 9-24



# **TOOLS - RENTAL EQUIPMENT**

N	<ul> <li>Portable hand notcher for use with our Loc Seam panel profiles</li> </ul>						
	<ul> <li>Durable steel construction</li> </ul>						
	<ul> <li>Use for quick notching of trim pieces requiring cutouts to accommo-</li> </ul>						
	date the panel ribs						
	<ul> <li>Replacement punch &amp; Die Set available for purchase</li> </ul>						
		SKU	Panel Profile	Pan	el Max. Ga.		
		RNOTCHL	Loc Seam		24		
LOC SEAM PANEL NOTC	HEK	TOONOTCHLPD Replacement Punch & Die Set					
	<ul> <li>Makes quick, easy, uniform bends along the drip edge of a flat pan standing seam roof panel</li> <li>Can be set to variable depths of 3/4", 1", 1-1/4", and 1-1/2" to accommodate a wide range of panel rib heights</li> <li>Reinforced steel plates for durability</li> <li>Removable ergonomic handle for ease of use and easy storage</li> <li>Contact surfaces are coated to prevent finishes from marring and scratching</li> </ul>						
			SKU	Width	Panel Max. Ga.		
DI PAN FOLDING TOOL			RFOLDDI	18″	22		